

1060867

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-135-23,046-6600

W/2-NE NW SEC. 15, T 16 S, R 26 W/E

4620 feet from S section line

3630 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5804

Lease Name Stecklein Well # 1

Operator: Dreiling Ltd. of Colo.

County Ness 149-18

Name & Address 410 17th St., #1140

Well Total Depth 4590 Mississippi feet

Denver, Co 80202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 300

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor R & C Drilling Co., Inc. License Number 9087

Address Box 296, Hays, Ks 67601

Company to plug at: Hour: 1 a.m. Day: 16 Month: 8 Year: 19 86

Plugging proposal received from John Wise with R. & C. Drilling

(company name) R & C Drilling (phone) 913-625-4548

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2612, GL  
Anhydrite 2090'

1st plug at 2080' with 50 sx cement

2nd plug at 1240' with 80 sx cement

3rd plug at 330' with 40 sx cement

4th plug at 40' with 10 sx cement 5th plug to circulate rathole with 15 sx cement

Plugging Proposal Received by Paul Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 5:15 am Day: 16 Month: 8 Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 2090' with 50 sx cement, 2nd plug at 1240' with 80 sx cement, 3rd plug 330' with 40 sx cement, 4th plug 40' with 10 sx cement, and 5th plug to circulate the rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix with 6% gel pumped by Halliburton.  
(If additional description is necessary, use BACK of this form.)

**INVOICED** (check) (if) observe this plugging.

DATE 8-20-86

AUG 20 1986

Signed Paul A. Luthi  
(TECHNICIAN)

INV. NO. 14775

8-20-86