

1090374

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-22,908-0000

NW SW NE , SEC. 21 , T 16 S, R 26 W/8  
3630 feet from S section line  
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5190

Lease Name Peters Well # 1

Operator: Sabre Exploration, Inc.  
Name & Address 310 W. Central, Suite 214  
Wichita, KS 67202

County Ness 149.83

Well Total Depth 4610 Mississippi feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 260

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Republic Drilling, Inc. License Number 9943

Address 310 W. Central, Suite 214, Wichita, KS 67202

Company to plug at: Hour: 9:00 pm Day: 8 Month: September Year: 19 85

Plugging proposal received from Joe Hemphill

(company name) Republic (phone) 316-264-0079  
Elevation 2635

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2052-2084

1st plug at base of the Anhydrite (approx. 2000) with 50 sx cement

2nd plug at 1200' with 80 sx cement

3rd plug at 275' with 50 sx cement  
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

Plugging Proposal Received by Robert B. Tarbutton  
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 11:30 pm Day: 8 Month: September Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 2084' with 50 sx cement, 2nd plug at 1200' with 80

sx cement, 3rd plug at 275' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with

15 sx cement.

Remarks: Used 60/40 Pozmix. 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED

SEP 17 1985

DATE

INV. NO.

10134

9-8 OCT 0 9 1985

RECEIVED STATE CORPORATION COMMISSION

SEP 16 1985

CONSERVATION DIVISION  
Wichita, Kansas

Signed

Robert B. Tarbutton  
(TECHNICIAN)

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 9 / 1 / 85 month day year

API Number 15- 135-22,908-0000 East NW SW NE Sec. 21 Twp. 16 S. Rg. 26 West 3630 Ft. from South Line of Section 2310 Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

OPERATOR: License # 5190 Name Sabre Exploration, Inc. Address 310 W. Central, Suite 214 City/State/Zip Wichita, Kansas 67202 Contact Person Matt Totten Phone 264-2635

Nearest lease or unit boundary line 330 feet County Ness Lease Name Peters Well # 1 Ground surface elevation 2635 est. feet MSI. Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 1 2X Depth to bottom of fresh water 100 Depth to bottom of usable water 200 1000 Surface pipe planned to be set 250 Projected Total Depth 4550 feet Formation Mississippian

CONTRACTOR: License # 9943 Name Republic Drilling, Inc. City/State Wichita, Kansas

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 8/19/85 Signature of Operator or Agent Title

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required feet per Alt. 1 2 This Authorization Expires 2-19-86 Approved By

Motion 9-1-85

878 @ 250'

The production string will be immediately cemented from below the surface. PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Base of Annhy 1st plug @ 1700 2000 feet depth with 50 sxs of 60/40 pozmix (3% gel) 2nd plug @ 1400 1200 feet depth with 40 80 sxs of 3rd plug @ 275 feet depth with 50 sxs of 4th plug @ 40 feet depth with 10 & solid bridge sxs of 5th plug @ feet depth with sxs of (2) Rathole with 15 sxs (b) Mousehole with sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. Important: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only: API #15- Legal, T, S, R Surface casing of feet set with sxs at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sxs on 19 Hole plugged 19, agent

1st 2084 w/ 50 sxs 7.D. 4610 miss. Any. 2052 Form 5-10-84 2nd 1200 w/ 80 sxs 878 260' AI. 2635' 3rd 275 w/ 50 sxs - STATE CORPORATE COMMISSION 11:30 AM - 9-8-85 RECEIVED SEP 10 1985 CONSERVATION DIVISION Wichita, Kansas