15-077-10209-00-00

Form CP-3
Rev. 6-26-62

KANSAS STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

RECEIVED STATE CORPORATION COMMISSION

J. P. Roberts
Assitant Director
500 Insurance Building
212 North Market
Wichita 2, Kansas

APR 7 1984 O4-07-1964 CONSERVATION DIVISION Wichita, Kansas

Well Plugging Supervisor

| Operator's Full Name_ | Messmar | n-Rinehart Oil Company | |
|---|-------------|--|---------------------|
| Complete Address: | 518 Petrole | um Bldg., Wichita, Kansas | |
| Lease Name | Hall | Well No. | # 2 |
| Location | NW NE NW | Sec. 28 Twp. 31 Re | $ge{7}(E)_{W}$ |
| County H | arper | Total Depth 468 | 8 (Simpson Sand) |
| | | Input Well SWD Well Elmination of the Mississ a Dual Completion Well | D&A ippi Lime in |
| Plugging Contractor: Halliburton Cementing Company | | | |
| Address: Pr | att, Kansas | Lice | ense No. |
| Operation Completed: Hour 4:30PM Day 31st Month March Year 1964 | | | |
| The Above well was plugged as follows: | | | |
| 4684' of 5%" long string, set open hole in Simpson Sand. Perferations | | | |
| in Mississippi were from 4313' to 4319'. Plug was set at 4382', and | | | |
| packer was set at 4290'. This was squeezed with 100 sacks of cement. | | | |
| to a pressure of 4,000 lbs, 90' up from the plug. | | | |
| Production packer was at 4635', to be knocked out. | | | |
| | | | |
| | | | |
| | | | |
| I hereby certify that the above well was plugged as herein stated. Signed: | | | |