TATE OF KANSAS		WELL PLUGGING RECORD K.A.R62-3-117			API NUMBER 15077 21,256-00-00				
00 Colorado Derby lichita, Kansas 67	Building "	-		×				Hoopes	
		TYPE OR	FRINT		WELL NUM	BER	1–19		
ža.		: fill ou return t						Section	
in .		ice withi			4950				
 ASE OPERATOR M	cCoy Petroleum Corp	oration						5 (E)o	
DORESS 110 S. Main	COUNTY Harper								
HONE (316) 265-9697 OPERATORS LICENSE NO. 5003						! Comp	pleted	5-13-92	
iaracter of Wellig					Plugging	Comme	enced _	5–13–92	
	, input, Water Sup	ply Well)			Plugging	Comp	leted _	5-13-92	<u> </u>
	sai was approved on			2				(4	ate)
	(Wichita KCC)				(XCC	Distr	rict Ag	entis Na	ge).
	YesIf not, I	s well to	g attac	:hed?					
)								
	kness of all water								
OIL, GAS OR WATER	•		<u> </u>		SING RECOR	lD			
	ILE COMO C								
		From T	o ISI		Put In	Pulled	d out	<u> </u>	
			1				d out		
			1						
Formation	Content the manner in which	.U 2	284 8-	-5/8 ugg•c	284	ng whe	ere the	mud flu	ild r pl
escribe in detail laced and the mail	Content	th the well	1 was producing	-5/8 plugged plece	i, Indicating the hole of, from	ng who	coment to	mud flut or other each	h s cemen
escribe in detail laced and the material brig. mud to 950'	the manner in which the character of 35 sx cement, drile	th the well of in intra same and to in rat bol	1 was producing	-5/8 plugged plece	i, Indicating the hole of, from ment, drile mix 4% ge	ng who	to 335	mud flu for other feet each '35 sx (h s cemer
escribe in detail laced and the mailer used, state Drlg. mud to 950'	the manner in which the character of 35 sx cement, drile	th the well of in intra same and to in rat bol	1 was producing	-5/8 plugged plece	i, Indicating the hole of, from ment, drile mix 4% ge	ng who	coment to	mud flu for other feet each '35 sx (h s cemer
escribe in detail laced and the mail ere used, state Drlg. mud to 950' Drlg. mud to 60' 2	the manner in which had or methods use the character of	th the well of in intra same and to in rat bol	i was i depth 660' 3'	olugged gltir plec 5 sx ce	i, Indication to the hole of, from ment, drile of mix 4% ge	ng who	to 335 nted by	mud flu for other feet each '35 sx (h s cemer
escribe in detail laced and the metal price used, state Drig. mud to 950' Drig. mud to 60' 2	the manner in whice the character of 35 sx cement, drile 25 sx cement 10 sx center of 35 sx center	in the well and to in rat bol	i was i depth 660' 3'	olugged gltir plec 5 sx ce	i, Indicating the hole of, from ment, drile mix 4% ge	ng who	to 335 nted by	mud flu for other feet each '35 sx (h s cemer
escribe in detail laced and the mail ere used, state Drlg. mud to 950' Drlg. mud to 60' 2 ame of Plugging C. ddress Haysy	the manner in which had ar methods use the character of 35 sx cement, drild 25 sx cement 10 sx wille, KS	in the well and to in rat bol	i was i depth 660' 3'	olugged It in plectors SX Ce -60 poz	i, Indication to the hole ment. drile mix 42 ge	ng who	to 335 ntod by	mud flu for othe feet each i' 35 sx (, Hallibur 5822	th s
escribe in detail laced and the material state of plugging Canada the series of plugging Canada the series of plugging Canada the series of party response that of KANSA McCo	the manner in which had ar methods use the character of 35 sx cement, drild 25 sx cement 10 sx wille, KS	tion	1 was 1 coducing 660' 35 An.	-5/8 Dlugged J t in plect 5 SX Ce -60 poz	i, Indication to the hole ment, drile mix 4% ge	ng who if feet ration	to 335 ntod by	mud flut or other test as the second or coperation of the second or coperation or cope	tor: