

325  
R

1 070577

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-23,272-0000  
NE NE SW, SEC. 24, T 16 S, R 26 WK  
2310 feet from S section line  
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 7200

Lease Name W.A. Jones Well # 3

Operator: Scott T. Lutz  
Name & Address P.O. Drawer D  
Shell Knob, MO 65747

County Ness 149.21  
Well Total Depth 4591 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 311

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Cheyenne Well Service License Number 6454

Address Ness City, KS

Company to plug at: Hour: 2:45 p.m. Day: 25 Month: 8 Year: 19 88

Plugging proposal received from Paul Cambron

(company name) Cheyenne Well Service (phone) 913-798-2282

were: 5 1/2" at 4587' Perfs at 4543-47, 4530-37, 4524-26'

RECEIVED  
STATE CORPORATION COMMISSION

1st plug pump 400 lbs. hulls and 154 sx ATL down 5 1/2"

2nd plug pump 100 sx ATL down 8 5/8"

AUG 31 1988  
8-31-88  
CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Dan Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 4:15 p.m. Day: 25 Month: 8 Year: 19 88

ACTUAL PLUGGING REPORT

1st plug pump 400 lbs. hulls and 154 sx ATL cement down 5 1/2"

2nd plug pump 100 sx ATL cement down 8 5/8"

Maximum pressure 700 psi and shut in 300 psi. 5 1/2"

Maximum pressure 200 psi and shut in 50 psi. 8 5/8"

Remarks: Used ATL cement by Allied. No casing recovery.  
(if additional description is necessary, use BACK of this form.)

INVOICED (with exception) observe this plugging.

Signed Dan Goodrow  
(TECHNICIAN)

DATE 9-8-88

INV. NO. 22148  
8-25