To:		API NUMBER 15- 007-20,840-4-00-0 i
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		NE SE , SEC. 11 , T 32 S, R 10 W/R
		1980 feet from S section line
TECHNICIAN'S PLUGGING REPORT		
Operator	License # 5004	Lease Name Schreiner "B" Weil # 1
Operator: Name& Address	Vincent Oil Corporation	County <u>Barber</u> 155, P4 Well Total Depth 4795 (Viola) feet
	125 North Market, Suite 1110	Well Total Depth4795 (Viola) feet
	Wichita, KS 67202	Conductor Pipe: Sizefeet
		Surface Casing: Size 8 5/8 feet 244
Abandoned		Input WellSWD WellD&A_X
Other wel	It as hereinafter indicated	
	•	Services. Inc. License Number 5149
	P. O. Box 329, Pratt, KS 67124	
		29 Month: July Year:19 85
	proposal received from	
(company	name) Wheatstate	(phone) 316-672-7514 Elevation 1504
were: to	fill hole with heavy mud and spot	cement through drill pipe Did not hit Anhydrite
•	at 270° with 40 sx cement	
2nd plug	solid bridge hulls - plug at 40' cement to s	surface with 10 sx cement
	to circulate rat hole with 15 sx o	
5th plug	to circulate mouse hole with 15 s	v cement
oru bras		osal Received by Steve Durrant
	Frugging Frop	(TECHNICIAN)
Plugging	Operations attended by Agent?: A	None y
•••		29 Month: July Year:19 85
		with 40 sx cement, 2nd & 3rd plugs - solid
		surface with 10 sx cement, 4th plug to
		plug to circulate mouse hole with 15 sx cement.
CIICUIALE	e lat hole with 15 sx cement, 5th	RECEIVED
		STATE CORPORATION COMMIL'SION
		AUG 1 3 1985
		<u>US-15-1985</u>
Remarks:	Used 60/40 Pozmix 6% gel by BJ-T	itan CONSERVATION DIVISION Wichita, Kansas
v 0 14	(if additional description is	s necessary, use <u>BACK</u> of this form.)
A para	did not pubserve this plugging.	Stoned Stone Showout
Y -	ルートン	Stand A Poll Kliment

FORM CP-2/3 Rev.01-84