

15-077-20238-00-00

Form CP-3  
Rev. 6-4-68

KANSAS

STATE CORPORATION COMMISSION  
CONSERVATION DIVISION AGENT'S REPORT

RECEIVED  
STATE CORPORATION COMMISSION

FEB 26 1974

CONSERVATION DIVISION  
Wichita, Kansas

02-26-1974

J. Lewis Brock  
Administrator  
P. O. Box 17027  
Wichita, Kansas 67217

Operator's Full Name National Oil Co.

Complete Address Suite 550 200 W. Douglas Wichita, KS

Lease Name Coady Well No. 1

Location C NE/SW Sec. 12 Twp. 33 Rge. 6 (E) (W) W

County Harper Total Depth 4885

Abandoned Oil Well      Gas Well      Input Well      SWD Well      D & A X

Other well as hereafter indicated     

Plugging Contractor Gabbert & Jones Inc

Address 830 Sutton Place Wichita, KS License No.     

Operation Completed: Hour 1:30 PM Day 23 Month 2 Year 1974

The above well was plugged as follows:

247 ft 8 5/8 surface cemented with 225 sacks. Pump plug. 35 sacks  
cement to 225 ft. Mud to 40 ft, plug, 1/2 sack hulla, 13 sacks cement  
to surface. 2 sacks cement in rat hole.

Pumped by Halliburton Cementing Co Great Bend, KS

I hereby certify that the above well was plugged as herein stated.

DATE 2/27/74

INV. NO. 8647-W

Signed Russell B. Bixler  
Well Plugging Supervisor

State of Kansas



15-077-20238-00-00

## State Corporation Commission

## CONSERVATION DIVISION

(Oil, Gas and Water)

P. O. Box 17027 3830 S. Meridian  
WICHITA, KANSAS 67217

## VERBAL PERMIT FORM

(To Be Filed By Plugging Agent)

RECEIVED  
STATE CORPORATION COMMISSION  
FEB 26 1974  
02-26-1974  
CONSERVATION DIVISION  
Wichita, Kansas

J. Lewis Brock  
Administrator  
500 Insurance Building  
Wichita, Kansas 67202

Dear Sir:

Mr. Gallager of Gabbert & Jones Drig has this  
date requested permission to plug the following described well:

Mr. Gallager guarantees payment of the plugging fee.

Operator's full Name: National Oil Co.

Complete Address: Suite 550 200 W Douglas Wichita, KS

Lease Name: Coady Well No. 1

Location: G NE/SW Sec. 12 Twp. 33S Rge. 6 (E)(W) W

County: Harper Total Depth 4885 Oil Well

Gas Well  Input Well  SWD Well  D & A X Lost Hole

Mr. Gallager was instructed to plug the well as follows:

247 ft 8 5/8 surface cemented with 225 sacks. Pump plug

35 sacks cement to 225 ft. Mud to 40 ft, plug, 1/2 sack

hulls, 13 sacks cement to surface. 2 sacks cement in

rat hole.

Pumped by Halliburton Cementing Co Great Bend, KS

Very truly yours,

H. Russell Bickerton  
Conservation Division Agent