

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-007-21554-0000

NW SW NW, Sec. 33, T 32 S, R 11 W/E

\_\_\_\_\_ feet from N/S section line

\_\_\_\_\_ feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5050

Lease Name Hall Well # 1

Operator: Hummon Corporation  
Name & Address One Main Place  
Suite 400  
Wichita, Kansas 6720

County Barber

Well Total Depth 4468 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8" feet 216

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Clarke Corporation License Number 5105

Address 107 W. Fowler Medicine Lodge 67104

Company to plug, at: Hour: 9:00 am Day: 24 Month: Feb Year: 19 83

VERBAL PLUGGING ORDERS GIVEN TO Elmo Morgenstern

(company name) Clarke (phone) \_\_\_\_\_

were: 1st Plug Sand to 2800' and put 45x cement on top

2nd Plug 35x hulls - 10 gel - 705x cement

10 gel - 1 hull - 1 Plug - 100 5x cement

50/50 pozmix 4% gel 3% cc

4 1/2 at 2967' w/1005x

Signed Richard W. Lucey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:30 am Day: 24 Month: Feb Year: 19 83

ACTUAL PLUGGING REPORT Plugged as ordered in above paragraph

Maximum Pump Pressure 200 psi

Shut in Pressure 100 psi

Recovered 2481' of 4 1/2" production casing

Allied cementing did the cement work

Remarks: Mr Robert Tarbutton gave plugging orders  
Mr Bud Metz witnessed the plugging work

I hereby certify that the above plugging instructions were given as herein stated and that I (~~did~~/ did not) observe this plugging.

INVOICED

DATE 3-23-83

INV. NO. 3592-W

STATE RECEIVED  
CORPORATION COMMISSION  
MAR 3 1983  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Richard W. Lucey  
(TECHNICIAN)

FORM CP-2/3  
Rev. 9-82