

15-077-20936-0000

SIDE TWO -

OPERATOR Eagle Explorations, Inc. LEASE Smith 1-26

ACO-1 WELL SEC. 26-TWP. 32 RCL

FILL IN WELL INFORMATION AS REQUIRED:

WELL NO.

Show all important zones of porosity and contents thereof; cored intervals, and all drill stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TO	BOTTOM	NAME	DEPTH
<input type="checkbox"/> Check if no Drill Stem Tests Run <input type="checkbox"/> Check if samples sent to Geological Survey DST #1 3720-3742 Stalnaker 30-60-3-60 GTS 3" 8" ga. 2.558 MMcfpd 18" ga. 3.752 MMcfpd 28" ga. 3.931 MMcfpd Heavy Spray saltwater 25" Rec. 255' S.W. (105,000 ppm cl) IFP 840-973 FFP 851-851 ISIP 1353 FSIP 1353 BHT 110°F			Heebner Douglas Iatan Stalnaker	3407 3454 3720 3722

RELEASED
OCT 12 1984
FROM CONFIDENTIAL

If additional space is needed use Page 2,


Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 1/4"	8 5/8"	24#	302'	Class "A" Com.	200	2% Gel. 3% CaCl
Production	7 7/8"	5 1/2"	14#	3958'	Class "H"	150	10% Salt, 10# per sack, Gilsonite, 75% Turbliance Induser.

LINER RECORD			PERFORATION RECORD		
Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD					
Size	Setting depth	Packer set at			
2 3/8"		NONE	4	22 Gram Slotted Chisels	3721-3726

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD		Depth interval
Amount and kind of material used		
NONE		

Date of first production	Producing method (flowing, pumping, gas lift, etc.)	Gravity
	Flowing	
Estimated Production -I.P.	Gas	Water
0 bbls.	1,600 MCF	NONE bbls.
Disposition of gas (vented, used on lease or sold)	Perforations	Gas-oil ratio
	3721-3726	NA CFPB



K. G. S. LIBRARY



COMPENSATED NEUTRON LITHODENS



COMPANY: **C** EAGLE EXPLORATIONS COMPANY
 WELL: 15-077-20936-0000
 SMITH PROSPECT #1-26

FIELD: ATTICA SOUTH WEST
 COUNTY: HARPER
 STATE: KANSAS
 NATION: USA
 LOCATION: C N/2 SW
 1980' FSL & 1320' FWL
 SEC: 26 TWP: 32 S RGE: S

RELEASE
NO SMALL S

Confidential

PERMANENT DATUM: GROUND LEVEL ELEVATIONS-
 ELEV. OF PERM. DATUM: 1455.0 KB: 1465.
 LOG MEASURED FROM: K.B. DF: 1463.
 10.0' ABOVE PERM. DATUM GL: 1455.
 DRLG. MEASURED FROM: KELLY BUSHING

DATE: 12 SEP 1983
 RUN NO: 1

DEPTH-DRILLER: 3960.0
 DEPTH-LOGGER: 3956.0
 BTM. LOG INTERVAL: 3954.0
 TOP LOG INTERVAL: 300.0

CASING-DRILLER: 302
 CASING-LOGGER: 294
 CASING: 8 5/8"
 WEIGHT: 24.00 LB/F
 BIT SIZE: 12 1/4" 7 7/8"
 DEPTH: 302 3960

K. G. S. LIBRARY