

1 090433

6-6

API NUMBER 15-007-22,442-00-00  
App. 100' W of  
NE SW SW, SEC. 7, T 33 S, R 12  
990 feet from S section line  
4390 feet from E section line

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 8061  
Operator: Oil Producers, Inc. of Kansas  
Name & Address: P.O. Box 8647  
Wichita, KS 67208

Lease Name Alexander B Well # 2  
County Barber  
Well Total Depth 3840 124.80 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 226

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A  X  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Duke Drilling Co., Inc. License Number 5929  
Address 310 W. Central, Wichita, KS 67202

Company to plug at: Hour: 5:15 p.m. Day: 6 Month: 6 Year: 19 94

Plugging proposal received from Joe  
(company name) Duke Drilling Co., Inc. (phone) 316-267-1331

Work: to fill hole with heavy mud and spot cement through drill pipe  
1st plug at 700' with 50 sx cement,  
2nd plug at 250' with 50 sx cement, 3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None  X

Operations Completed: Hour: 6:15 p.m. Day: 6 Month: 6 Year: 19 94

ACTUAL PLUGGING REPORT 1st plug at 700' with 50 sx cement,  
2nd plug at 250' with 50 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
5th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 6-27-94

NO. 40638 AUG 11 1994

RECEIVED STATE CORPORATION COMMISSION JUN 28 1994 CONSERVATION DIVISION Wichita, Kansas Signed (TECHNICIAN)