

5-9

35

To: 1 120563
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 13- 135-23,570-000
C SE SE, SEC. 15, T 20 S, R 22 W/E
660 feet from S section line
660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5316
Operator: Falcon Exploration, Inc.
Name & Address 125 N. Market, Suite 1075
Wichita, KS 67202

Lease Name Hanna Well # 1
County Ness 143.26
Well Total Depth 4408 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 665

Abandoned Oil Well Gas Well Input Well SWD Well D&A X
Other well as hereinafter indicated

Plugging Contractor Blue Goose Drilling Company License Number 5104
Address P.O. Box 1413, Great Bend, KS 67530

Company to plug at: Hour: 7:30 p.m. Day: 9 Month: 5 Year: 19 91
Plugging proposal received from Martin Miller
(company name) Blue Goose Drilling Company (phone) 316-792-5633

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1472-1504'
1st plug at 1520' with 50 sx cement, 2nd plug at 750' with 75 sx cement,
3rd plug at 351' with 40 sx cement, 4th plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Duane Rankin
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X
Operations Completed: Hour: 10:15 p.m. Day: 9 Month: 5 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug at 1520' with 50 sx cement,
2nd plug at 750' with 75 sx cement,
3rd plug at 351' with 40 sx cement,
4th plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION
MAY 13 1991
5-13-91
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel 1/4# floseal by Allied.
(If additional description is necessary, use BACK of this form.)

INVOICED
DATE 5-29-91
INV. NO. 31936

Signed Duane Rankin
(TECHNICIAN)

FORM MUST BE TYPED
FORM C-1 4/90

EFFECTIVE DATE: 4-20-91

State of Kansas
NOTICE OF INTENTION TO DRILL

135-23,570-0000

FORM MUST BE SIGNED
ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 4 26 91
month day year

...C... SE. SE. Sec. 15. Twp. 20. S, Rg. 22 X East West

660 feet from South line of Section
660 feet from East line of Section
(Note: Locate well on Section Plat on Reverse Side)

OPERATOR: License # 5316
Name: Falcon Exploration, Inc.
Address: 125 N. Market, Suite 1075
City/State/Zip: Wichita, KS 67202
Contact Person: Jim Thatcher
Phone: (316) 265-3351

County: Ness
Lease Name: Hanna Well #: 1
Field Name: wildcat
Is this a Prorated Field? yes X no
Target Formation(s): Mississippi
Nearest lease or unit boundary: 660
Ground Surface Elevation: 2234 feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water: 320
Depth to bottom of usable water: 625
Surface Pipe by Alternate: X 1 2
Length of Surface Pipe Planned to be set: 200
Length of Conductor pipe required: 0
Projected Total Depth: 4350
Formation at Total Depth: Mississippi
Water Source for Drilling Operations:
... well ... farm pond X other

CONTRACTOR: License #: 5104
Name: Blue Goose Drilling Co.

Well Drilled For: Well Class: Type Equipment:
X Oil ... Inj ... Infield X Mud Rotary
... Gas ... Storage ... Pool Ext. ... Air Rotary
... OWWO ... Disposal X Wildcat ... Cable
... Seismic; ... # of Holes

If OWWO: old well information as follows:

Operator: ...
Well Name: ...
Comp. Date: ... Old Total Depth ...

Directional, Deviated or Horizontal well bore? yes X no
If yes, total depth location: ...

Exp. 10/15/91

RECEIVED
STATE CORPORATION COMMISSION

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following minimum requirements will be met:

1. The appropriate district office within Kansas

* 700' of surface pipe required

Pusher Martin Miller

SPUD DATE 4-30-91 INIT. R.L.

LENGTH SURFACE PLANNED 650

RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8" @ 665 CONDUCTOR
ANHYDRITE T-1472 B-1504 ELEVATION

TD 4408 FORMATION

RAN PIPE @ DV TOOL ALT II DONE
SX Y N

Arbuckle Plug @ Ft. W/ SX

Hug./Council @ Ft. W/ SX

Anhydrite Base @ 1520 Ft. W/ 50 SX

1/2 Base Anyh. @ 750 Ft. W/ 15 SX

1/2, 1/2 Plug @ 357 Ft. W/ 40 SX

Bottom Surface @ Ft. W/ SX

40' Plug @ 40 Ft. W/ 10 SX

RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ SX

WATER WELL SX (Irr. Well Pond Hauling)

TECHNICIAN DATE

TYPE OF CEMENT 66-46-6 4

STARTING TIME 7:30 (AM/PM) DATE 5-9-91

COMPLETION TIME 10:15 (AM/PM) DATE 5-9-91

CEMENT COMPANY Allied