

K-007-10198-0000

STATE OF KANSAS  
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
211 No. Broadway  
Wichita, Kansas

Barber County. Sec. 29 Twp. 31S Rge. 14W (E) (W)

Location as "NE/CNW/SW" or footage from lines SW SW NW

Lease Owner West Supply Co., Inc.

Lease Name H. W. Skinner "B" Well No. 4

Office Address Box 506 - Chase, Kansas

Character of Well (completed as Oil, Gas or Dry Hole) Oil well

Date well completed August 21 19 57

Application for plugging filed May 25 19 57

Application for plugging approved May 27 19 57

Plugging commenced June 10 7 19 57

Plugging completed June 13 19 57

Reason for abandonment of well or producing formation Depleted.

If a producing well is abandoned, date of last production January 19 57

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Merle Rives

Producing formation \_\_\_\_\_ Depth to top \_\_\_\_\_ Bottom \_\_\_\_\_ Total Depth of Well 4586 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				10-3/4"	310'	None
				7" OD	4578'	3013'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

Filled the hole with sand from 4586' to 4570'  
and ran 5 sacks of cement. Pulled casing up to  
1600' and circulated the hole with 42 sacks of  
jell mud. Pulled rest of casing. Mudded the hole  
to 300', set a 10' rock bridge and ran 25 sacks  
of cement. Mudded the hole to 25', set a 5' rock  
bridge and ran 10 sacks of cement to the base of  
the cellar. Plugging completed.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor West Supply Co., Inc.

Address Chase, Kansas

STATE OF Kansas, COUNTY OF Rice, ss. E. E. O'Brien (employee of owner) or (~~owner~~) of the above-described

well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) E. E. O'Brien

Chase, Kansas  
(Address)

SUBSCRIBED AND SWORN TO before me this 18th. day of June, 19 57

My commission expires 9-27-58

Thomas V. Duggin  
Notary Public.

STATE CORPORATION COMMISSION

PLUGGING  
FILE SEC. 29 T. 31 R. 14W  
BOOK PAGE 15 LINE 32

JUN 19 1957  
6-19-57  
CONSERVATION DIVISION  
Wichita, Kansas

15-007-10198-0000

Well No. 4 H. W. Skinner "B" Farm

Sec. 29 Twp. 31S Range 14W

Drilling Contractor R.C. Patton Drilling Co.

Burber County KANSAS State 320 Acres

Drilling Commenced July 21 19 47

Use No. Sec. 29-31S-14W

Drilling Completed August 21 19 47

Commenced Production August 21 19 47


Natural Production First 24 hours 8hrs 100 bbls

Natural Production Second 24 hours bbls

T. D. 4586'

RECORD OF PAY SAND

Viola Lime	4578	4586	Pay
Schlumberger log in folder.			



Elev. D.F. 1801' Gr. 1799'

Feet from N. line	Feet from E. line
Feet from S. line	Feet from W. line
Fresh water from	to
Salt water from	to
Salt water from	to
Salt water from	to

Wooden Conductor-Size Feet

DRIVE PIPING, CASING, TUBING AND RODS

Size	WL per Ft.	Put In	Pulled Out
10-3/4"	32.75#	310'	
7"	23#	4575'	
10-3/4"	This and new electric well cemented with 3 sacks.		
7"	This and J-1 cemented with 250 sacks 3/4 Aquagel.		

TORPEDO RECORD

Date of Shot	Qts.	Top Shot	Box Shot	Remarks
8-23-47		4578	4586	Acidized with 2000 gals 15% acid thru tubing. Top treating pressure 1150#. Well went on vacuum after pumps shut down. Before treating, well flowed at rate of 300 bbls per day thru 7" casing. After treating, well flowed 281 bbls in 13hrs thru 2" tubing, 32/64" choke. Potential 3359 bbls.

Packer set at	Size and Kind
Packer set at	Size and Kind
Packer set at	Size and Kind
Water well Contractor furnish	Feet at \$ per foot
Price of Contract \$ 4.50	per foot & mud up to \$500.00
Approved <i>Richard A. Keeney</i>	Vice-President in Charge of Production

Note: All measurements from top of rotary bushing which was 7'2" above top of lower flange on breadinghead.

MAY 27 1957  
5-27-57

**PLUGGING**  
FILE SEC 29-T-31-R-14W  
BOOK PAGE 15 LINE 32

0	91	Red Shale and Sand
91	630	Red Red
630	700	Lime & Shale
700	880	Shale & Shells
880	1050	Red Rock
1050	1240	Shale & Shells
1240	1445	Salt
1445	1910	Shale & Shells
1910	1945	Shale
1945	2055	Lime
2055	2135	Lime & Shale
2135	2330	Lime
2330	2375	Lime Sandy
2375	2380	Lime & Shale
2380	2825	Lime
2825	3160	Lime & Shale
3160	3230	Lime
3230	3305	Lime & Shale
3305	3405	Lime
3405	3475	Lime & Shale
3475	3540	Lime
3540	3670	Lime & Shale
3670	3700	Lime
3700	3805	Lime & Shale
3805	3850	Lime
3850	3915	Lime & Shale
3915	3925	Shale
3925	3965	Lime & Shale
3965	3980	Sand & Shale
3980	4537	Lime
4537	4553	Lime & Shale
4553	4578	Shale
4578	4581	Lime
4581		T.D. of rotary hole. Drilled plug at 1000' depth in hole and C.C. to bottom. Well started showing signs thru water.
4581	4582	Lime Chert White hard. After standing overnight well 7500' plug in place.
4582	4583	Lime, white, hard. Drilled well 4582.
4583	4588	Lime, white, hard. Drilled well 4583. Plug in place. Well started showing signs thru water.
4588		

Formation tops as noted from samples by  
Delmar L. Powers, Geologist

	<u>Samples</u>	<u>Schiller</u>	<u>Letter</u>
Heebner Sh	379		
Douglas Series	3245		
Douglas Sand	3597		
Intan Ls	3956		
Lansing-Kansas City Ls	3975		
Basal Penn (Cherty) Congl.	4520		
Kinderhook Sh	4540		
Viola Ls (Maquoketa Dob)	4578		4577