

2 030092

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-077-20,983-0000

C NE NW, SEC. 35, T 32 S, R 9 W

660 feet from N section line

1980 feet from N section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5056

Lease Name Sanders Well # 1-35

Operator Name: F. G. Hall

County Harper

Address 6427 E Kellogg

Well Total Depth 4465 145.11 feet

Wichita, Ks. 67207

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8" feet 259'

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sterling Drilg. Co. License Number 5142

Address P.O. Box 129, Sterling, Ks. 67579

Company to plug at: Hour: 12:00MN Day: 28 Month: 4 Year: 1984

Plugging proposal received from Tom Meyers

(company name) Sterling Drilg. Co. (phone) \_\_\_\_\_

were: Fill hole/mud, run d.p. to 950' spot 35% cement, pull d.p. to 310', spot 35% cement, pull d.p. to 60', spot 25% cement, pump 10% cement in rat hole, + 5% cement in mouse hole.

Plugging Proposal Received by Don Thompson  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 3:30AM Day: 28 Month: 4 Year: 1984

ACTUAL PLUGGING REPORT Filled hole/mud, ran d.p. to 950', Halliburton Services # 858307, spotted 35% cement, pulled d.p. to 310', spotted 35% cement, pulled d.p. to 60', spotted 25% cement to run, pumped 10% cement in rat hole + 5% cement in mouse hole.

Remarks: \_\_\_\_\_  
(if additional description is necessary, use BACK of this form to observe this plugging.)

RECEIVED  
STATE CORPORATION COMMISSION  
MAY 08 1984  
5-8-84  
CONSERVATION DIVISION  
Wichita, Kansas

INVOICED

DATE 5-10-84

WV. NO. 1444

Signed Don Thompson  
(TECHNICIAN)