

STATE OF KANSAS  
STATE CORPORATION COMMISSION  
200 Colorado Derby Bldg.  
Wichita, Kansas 67202

RECEIVED  
STATE CORPORATION COMMISSION  
Rev. 12-15-80

APR 13 1982

CONSERVATION DIVISION  
Wichita, Kansas

WELL PLUGGING RECORD

Give All Information Completely  
Make Required Affidavit

COUNTY Harper SEC. 13 TWP. 32 S RGE. 8 E/W  
Location as in quarters or footage from lines:  
C- SE SE


Lease Owner McCoy Petroleum Company  
Lease Name Naffziger Well No. 1  
Office Address One Main Place- Suite 410- Wichita, Kansas 67202  
Character of Well (Completed as Oil, Gas or Dry Hole): oil-gas  
Date Well Completed 5-12-73  
Application for plugging filed 3-20-82  
Plugging commenced 3-29-82  
Plugging completed 4-2-82  
Reason for abandonment of well or producing formation  
Non Productive

Locate Well  
correctly on above  
Section Platt.

Was permission obtained from the Conservation Division or it's  
Agent's before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well M. V. Leslie  
Producing formation \_\_\_\_\_ Depth to top \_\_\_\_\_ bottom \_\_\_\_\_ T.D. 4,460  
Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

Casing Record

Formation	Content	From	To	Size	Put in	Pulled Out
				8 5/8	256	None
				4 1/2	4445	3594
<u>Mississippian</u>	<u>Gas</u>	<u>4445</u>	<u>4460</u>			

Describe in detail the manner in which the well was plugged, indicating where the mud  
fluid was placed and the method or methods used in introducing it into the hold. If cement  
or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet  
to \_\_\_\_\_ feet for each plug set.

Open hole - sand from 4,460 to 4,390  
4 sacks cement from 4.390 to 4,360

Ripped at 3,600. Pulled 4 1/2. Layed down  
Allied pumped in 15 sacks jel - 6 sacks hull - 10 sacks jel-  
150 sacks common cement - 3% C. C.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor Clarke Corporation


STATE OF KANSAS COUNTY OF Sedgwick, ss.  
Elmo H. Morgenstern (employee of owner) or (owner or operator) of the  
above-described well, being first duly sworn on oath, says: That I have knowledge of the  
facts, statements, and matters herein contained and the log of the above-described well as  
filed and that the same are true and correct. So help me God.

(Signature) Elmo H. Morgenstern  
(Address) \_\_\_\_\_

SUBSCRIBED AND SWORN TO before me this 12th day of April, 1982

Christina Louise Sollars  
Notary Public.

My Commission expires: 2-20-86



STATE OF KANSAS  
 STATE CORPORATION COMMISSION  
 200 Colorado Derby Bldg.  
 Wichita, Kansas 67202

Form CP-4  
 RECEIVED 2-15-80  
 STATE CORPORATION COMMISSION

APR 12 1982

CONSERVATION DIVISION  
 Wichita Kansas

WELL PLUGGING RECORD

Give All Information Completely  
 Make Required Affidavit

COUNTY Harper SEC. 13 TWP. 32 S RGE. 8 E/W  
 Location as in quarters or footage from lines:  
C- SE SE


Lease Owner McCoy Petroleum Company  
 Lease Name Naffziger Well No. 1  
 Office Address One Main Place - Suite 410- Wichita, Kansas  
 Character of Well (Completed as Oil, Gas or Dry Hole): oil  
 Date Well Completed 5-12-73  
 Application for plugging filed 3-20-82  
 Plugging commenced 3-29-82  
 Plugging completed 4-2-82  
 Reason for abandonment of well or producing formation Non Productive

67202

Locate Well  
 correctly on above  
 Section Platt.

Was permission obtained from the Conservation Division or it's  
 Agent's before plugging was commenced? yes

Name of Conservation Agent who supervised plugging of this well M. V. Leslie

Producing formation \_\_\_\_\_ Depth to top \_\_\_\_\_ bottom \_\_\_\_\_ T.D. 4,460

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

Casing Record

Formation	Content	From	To	Size	Put in	Pulled Out
				8 5/8	256	None
				4 1/2	4445	3594

Describe in detail the manner in which the well was plugged, indicating where the mud  
 fluid was placed and the method or methods used in introducing it into the hold. If cement  
 or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet  
 to \_\_\_\_\_ feet for each plug set.

Open hole - Sand from 4,460 to 4,390  
4 sacks cement from 4,390 to 4,360

Ripped 3,600. Pulled 4 1/2. Layed down.

Allied pumped in 15 sacks jel - 6 sacks hull - 10 sacks jel  
150 sacks common cement - 3% C. C.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor Clarke Corporation

STATE OF \_\_\_\_\_ COUNTY OF \_\_\_\_\_, ss.

(employee of owner) or (owner or operator) of the  
 above-described well, being first duly sworn on oath, says: That I have knowledge of the  
 facts, statements, and matters herein contained and the log of the above-described well as  
 filed and that the same are true and correct. So help me God.

(Signature) [Signature]  
 (Address) \_\_\_\_\_

SUBSCRIBED AND SWORN TO before me this \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_

Notary Public.

My Commission expires: \_\_\_\_\_

DAILY REPORT

McCoy Petroleum Company & Kedco Corp.  
 #1 Naffziger  
 C SE SE Sec. 13-32S-8W  
 Harper County, Kansas

Contractor: Sweetman Drilling, Inc. Rig #1

ELEVATIONS: 1428 GL 1435 DF 1438 KB

1/22/73	Waiting on mud.		
1/26/73	Moving in Rotary Tools.		
1/27/73	Moving in Rotary Tools.		
1/28/73	Shut down for weather.		
1/29/73	Will spud this morning. Spud @ 12:30 P. M. Set new 8-5/8" surface casing at 256' w/225 sx common cement, 2% gel, 3% calcium chloride. Plug down @ 7:30 P. M.		
1/30/73	Drilling @ 400'.		
1/31/73	Drilling @ 1645'.		
2/ 1/73	Drilling @ 2414'.	Heebner	3331(-1893)
		Douglas	3438(-2000)
2/ 2/73	Drilling @ 3002'.	Iatan	3602(-2164)
		Stalnaker	3662(-2224)
2/ 3/73	Drilling @ 3607'.	Kansas City	3905(-2467)
		Stark Shale	4040(-2602)
2/ 4/73	Drilling @ 4034'.	Cherokee	4304(-2866)
		Mississippi	4443(-3005)
2/ 5/73	Drilling @ 4320'.	T.D.	4460(-3022)