

**TQ:**  
**STATE CORPORATION COMMISSION**  
**CONSERVATION DIVISION - PLUGGING**  
**130 SOUTH MARKET, SUITE 2078**  
**WICHITA, KANSAS 67202**

**API Well Number:** 15-077-21411-00-00  
**Spot:** SWNENE      **Sec/Twnshp/Rge:** 20-34S-9W  
4290 feet from S Section Line, 990 feet from E Section Line  
**Lease/Unit Name:** SHROYER A      **Well Number:** 1-20  
**County:** HARPER      **Total Vertical Depth:** 4689 feet

**Operator License No.:** 5003      **Conductor Pipe: Size**      feet: 8 1/2 .39  
**Op Name:** MCCOY PETROLEUM CORPORATION      **Surface Casing: Size** 8.625      feet: 265      350 SX CMT  
**Address:** 453 S. WEBB RD. STE 310 PO BOX 78020      **Production: Size** 4.5      feet: 4684      175 SX CMT  
WICHITA, KS 67278      **Liner: Size**      feet:

**Well Type:** OIL      **UIC Docket No:**      **Date/Time to Plug:** 08/22/2002 10:15 AM  
**Plug Co. License No.:** 31925      **Plug Co. Name:** QUALITY WELL SERVICE, INC.  
**Proposal Rcvd. from:** JOE MAES      **Company:** QUALITY WELL SERVICE      **Phone:** (620) 272-1296

**Proposed Plugging Method:** See actual report.


**Plugging Proposal Received By:** STEVE VANGIESON      **WitnessType:** Plugging Operations Were Not Witnessed  
**Date/Time Plugging Completed:** 08/22/2002 10:15 AM      **KCC Agent:** STEVE VANGIESON

**Actual Plugging Report:**

The perms were covered w/sand to 4580' and capped w/4sxs cement. The pipe was recovered from well and pulled to 1350', spotted 35sxs cement. Pulled to 900' and spotted 35sxs cement. Pulled to 310' and circulated cement to surface.

RECEIVED  
KCC DISTRICT #2  
AUG 28 2002  
WICHITA, KS

**Remarks:** ACID SERVICES # 5144 60/40, 4% GEL.  
**Plugged through:** CSG

**District:** 02      **Signed**  \_\_\_\_\_  
(TECHNICIAN)

**INVOICED**  
**DATE** 8-28-02  
**INV. NO.** 2003060457