BASHEE

Form CP-3 Rev. 6-4-68

STATE CORPORATION COMMISSION

RECEIVED STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

JAN 15 1975

J. Lewis Brock Administrator P. O. Box 17027 Wichita, Kansas 67217

CONSERVATION DIVISION Wichita, Kansas

Location NW/SE/SE	S	ec. 24 Twp. 34 Rg	re. 13 (R)
County Barber		Total Depth	
	Well X Input W		
Other well as hereafter indicate			·
Plugging Contractor Clarke C			
Address Box 187 Medicine L		License N	583
Operation Completed: Bour 5:			
The shore well was always as as	-11		
The above well was plugged as fo			• _
355 ft 9 5/8 surface ceme	nted with 300 s	acks. 4909 ft	5g long
cemented with 150 sacks.	Top perf. 4796	ft. Sand to 4	7 <u>3</u> 5 ft, 5
cement with bailer. Pull	ed 3619 ft 54.	Pump 2 hulls,	10 gel, (
	~		
PACKS COMONT TO CUMPAGE	···		<u> </u>
sacks cement to surface.			
	nting Great Be	nd, KS	
sacks cement to surface. Pumped by Halliburton Ceme	nting Great Be	nd, KS	
	nting Great Be	nd, KS	
	nting Great Be	nd, KS	
	nting Great Be	nd, KS	
Pumped by Halliburton Ceme			
			В. 1 —
umped by Halliburton Ceme	well was plugged as	s herein stated.	Milas da Supervis