To: 1 040238 API NUMBER 15- 007-21,812-00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION W/2 NW NW , SEC. 8 , T 30 s, R 12 WAEX
WICHITA, KANSAS 67202 4620 feet from S section line
TECHNICIAN'S PLUGGING REPORT 4950 feet from E section line
Operator License # 5056 Lease Name Rose "A" Wall # 1-8
Operator:         F.G. Holl Company         County Barber         156.00           Name& Address         6427 East Kellogg RECENTION COMPANY         Well Total Depth 4800 feet           P.O. Box 78016 ATE COMPANY         Conductor Pipe: Size feet           Wichita, KS 67207 MAC ansign         Surface Content for 10 3/4 253
Name& Address 6427 East Kellogg RECEITON COMM. Well Total Depth 4800 feet
P.O. Box 78016ATE CORPORATION Conductor Pipe: Size feet  Wichita, KS 67207 M.C. Surface Casing: Size 10 3/4 feet 253  Abandoned Oil Well X Gas Watth Tight Surface Input Well SWD Well DIA
Wichita, KS 67207 MAC Surface Casing: Size 10 3/4 feet 253
Wichita, KS 67207 M. Surface Casing: Size 10 3/4 feet 253  Abandoned Oil Well X Gas Wath Name 1 SWD Well D&A  Other well as hereinafter indicated
Abandoned Oll Well X Gas Wath Kans Input Well SWD Well D&A
Plugging Contractor Pratt Well Service License Number 5893
Address P.O. Box 847, Pratt, KS 67124
Company to plug at: Hour: 1 p.m. Day: 14 Month: 3 Year: 19 89
Plugging proposal received from Bruce Wagner
(company name) Pratt Well Service (phone) 316-672-2531
were: 41/2" at 4798' PBTD 4370' Perfs at 4301-05'
1st plug sand back to 4250' and dump 4 sx cement on top of sand through bailer,
2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls,
release 10 3/4" wiper plug and pump 125 sx cement.
Plugging Proposal Received by Duane Rankin
(TECHNICIAN)
Plugging Operations attended by Agent?: All X Part None
Operations Completed: Hour: 1:30 p.m.Day: 14 Month: 3 Year:1989
ACTUAL PLUGGING REPORT 1st plug sanded back to 4160' and dumped 4 sx cement on top of
sand through bailer,
2nd plug pumped down 10 3/4" surface pipe with 400 lbs. hulls, 10 sx gel, 50 sx cement,
10 sx gel, 100 lbs. hulls, and 125 sx cement.
Maximum pressure 500 psi and shut in 350 psi.
THE PERSON NAMED IN SEC. 21. S
Personal Mond 60//0 Personal 6% cell by Welliburton Personal 22/71 of /bll enging
Remarks: Used 60/40 Pozmix 6% gel by Halliburton. Recovered 2247 of 4½" casing.  (If additional description is necessary, use BACK of this form.)
I Na Va On Cont. Deserve this plugging.
TE 3-23-89 Signed Stephen Touten

FORM CP-2/3 Rev.01-84