|   | 1090176   | D   |
|---|---|---|
| To:<br>STATE CORPORATION COMMISSION<br>CONSERVATION DIVISION - PLUGGING SECTION<br>200 COLORADO DERBY BUILDING<br>WICHITA, KANSAS 67202 |   | NE SW SE , SEC. 1 , 7 30 S, R 12 W            |
| TECHNICIAN'S PLUGGING REPORT  |   | 1650 feet from WYE section line               |
| Operator  | License # 8144                                  | Lease Name Gibson Well 1                      |
| Names   | Gunner Oil Company                              | County Barber                                 |
|   | 519 Parke                                       | Well Total Depth 3900 126.75 fee              |
|   | Pratt, KS 67124                                 | Conductor Pipe: Sizefeet                      |
|   |   | Surface Casing: Size 8 5/8 feet 298           |
| Abandoned   | OII Well Gas Well                               | Input Well SWD Well D&A X                     |
| Other wel   | t as hereinafter indicated                      |   |
| Plugging  | Contractor Aldebaran Drilling (                 | Co., Inc. License Number 5829                 |
| Address   | P. O. Box 18611, Wichita, KS 67                 | 7218  |
| Company to  | o plug at: Hour: 3:00 am Day:                   | 27 Month: May Year: 19 84                     |
| Plugging  | proposal received from                          | Mark Gwinn                                    |
| (company i  | name) Aldebaran                                 | (phone) 316-685-5372                          |
| WOFG:   | to fill hole with heavy mud and                 | spot cement through drill pipe                |
|   | at 840° with 50 sx cement                       |   |
| 2nd plug  | at 360' with 40 sx cement                       |   |
| •   | solid bridge<br>hulls - plug at 40' cement to   | surface with 10 sx cement                     |
|   | to circulate rat hole with 15 sx                |   |
|   | to circulate mouse hole with 10<br>Plugging Pro | sx cement posal Received by                   |
|   |   | (TECHNICIAN)                                  |
| Plugging (  | Operations attended by Agent?:                  | AllPartNone_X                                 |
| Operation   | s Completed: Hour: 5:15 am Day:                 | 27 Month: May Year: 19 84                     |
| ACTUAL PL   | UGGING REPORT 1st plug at 8                     | 340' with 50 sx cement, 2nd plug at 360' with |
| 40 sx cem   | ent, 3rd & 4th plugs - solid bri                | idge - hulls - plug at 40' cement to surface  |
| with 10 s   | x cement, 4th plug to circulate                 | rat hole with 15 sx cement, 5th plug to       |
| circulate   | mouse hole with 10 sx cement.                   | RECEIVED STATE CORPORATION COMMISSION         |
|   |   | JUN 0 1 1984                                  |
| Remarks:  | Use 60/40 Pozmix 2% gel 3% cc by                | Allied #32647 CONSERVATION DIVISION           |
|   | (If additional description i                    | s necessary, use BACK of this formula Kansas  |
| \A.Q.\()  | dia not) observe this plugging.                 | DREDA Gotto                                   |

FORM CP-2/3 Rev.01-84