

1 040487

11-26 15-007-01423-00-00
API NUMBER 15- Drill Completion Date 9/20/58

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

NE NE, SEC. 35, T 34 S, R 13 W/E
4620 feet from S section line
660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 3048

Lease Name Ed Sterling Well # 2

Operator: Bristol Resources Corporation
Name & Address: 6655 S. Lewis, Suite 200
Tulsa, OK 74136

County Barber 159.73

Well Total Depth 4915 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 274

Abandoned Oil Well X Gas Well Input Well SMD Well D&A

Other well as hereinafter indicated

Plugging Contractor Clarke Corporation License Number 5105

Address Medicine Lodge, KS

Company to plug at: Hour: 11 a.m. Day: 26 Month: 11 Year: 19 90

Plugging proposal received from Jeff Clarke

(company name) Clarke Corporation (phone) 316-886-5665

were: 5 1/2" at 4913' w/150 sx cement, PBSD 4912', Perfs at 4840-84'

1st plug plug back to 4600' and dump 5 sx cement on top of sand bridge through bailer,
2nd plug pump down 8 5/8" surface pipe with 300 lbs. hulls, 10 sx gel, 50 sx cement,
10 sx gel, 100 lbs. hulls, release 8 5/8" wiper plug and pump 100 sx cement.

Plugging Proposal Received by Steve Pfeifer (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part None

Operations Completed: Hour: 11:45 a.m. Day: 26 Month: 11 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 5 sx cement on top of sand bridge through bailer.

2nd plug pumped down 8 5/8" surface pipe with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.

Maximum pressure 400 psi and shut in 300 psi.

Remarks: Used 60/40 Pozmix 6% gel by B.J. Services. Recovered 26000 cu of 5 1/2" casing.
(If additional description is necessary, use BACK of this form.)

INVOICED (If applicable) observe this plugging.

DATE 12-7-90

INV. NO. 30184

Signed Steve Pfeifer (TECHNICIAN)