WELL COMPLETION FORM

	٠.			Sept	emb	er 199
			Form	Must	Ве	Type
2	K.,	2000				

	PLETION FORM
WELL HISTORY - DESC	RIPTION OF WELL & LEASE 9-25-07 KCC WICHERD ICINIA
Operator: License # 3532	KCC WICHOR GINA
Name: CMX, Inc.	
Address: 150 N. Main - Suite 1026	W/2 SE NE Sec. 29 Twp. 31 S. R. 11 East Wes
City/State/Zip: Wichita, Kansas 67202	feet from S / N (circle one) Line of Section
Purchaser:	990 feet from E/ W (circle one) Line of Section
Operator Contact Person: Douglas H. McGinness II	Footages Calculated from Nearest Outside Section Corner:
Phone: (<u>316</u>) <u>269-9052</u>	(circle one) (NE) SE NW SW
Contractor: Name: Duke Drilling Co., Inc.	Lease Name: Whelan "OWWO" Well #: 1-
License: 5929	Field Name: Whelan ext.
Wellsite Geologist: Douglas H McGinness II	
Designate Type of Completion:	Elevation: Ground: Kelly Bushing:
New Well X Re-Entry Workover	Total Depth: 3835 Plug Back Total Depth:
Oil SWD SIOW Temp. Abd.	Amount of Surface Pipe Set and Cemented atexisting @ 215Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used?
X Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
f Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from
Operator: Graves Drilling	feet depth tosx cmt.
Well Name: #2 Whelan	0.46.0024
Original Comp. Date:6-17-77 Original Total Depth: 4412*	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	Chloride content ppm Fluid volume bbls
Plug Back Plug Back Total Depth	Dewatering method used
Commingled Docket No.	_
Dual Completion	Location of fluid disposal if hauled offsite:
Other (SWD or Enhr.?) Docket No	Operator Name:
08-01-02 08-01-02 8/1/02	Lease Name: License No.:
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West
Recompletion Date Recompletion Date	County: Docket No.:
	·
Kansas 67202, within 120 days of the spud date, recompletion, workor information of side two of this form will be held confidential for a period of	th the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, ver or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. 12 months if requested in writing and submitted with the form (see rule 82-3-s and geologist well report shall be attached with this form. ALL CEMENTING s. Submit CP-111 form with all temporarily abandoned wells.
Kansas 67202, within 120 days of the spud date, recompletion, workon information of side two of this form will be held confidential for a period of 107 for confidentiality in excess of 12 months). One copy of all wireline log TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged well	ver or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. 12 months if requested in writing and submitted with the form (see rule 82-3-s and geologist well report shall be attached with this form. ALL CEMENTING

Signature: Subscribed and sworn to before me this $\underline{-23}$ XX 2002.

Date Commission Expires:

Notacy Public - State of Kansas

KCC Office Use ONLY

Letter of Confidentiality Attached

Il Denied, Yes Date:

Wireline Log Received

Geologist Report Received UIC Distribution

Operator Name:	X, Inc.		Lease Name	Whelan "(OWWO"	Well #:2	, r
		East West		arber County	y, Kansas		
ested, time tool oper emperature, fluid red	and closed, flowir	and base of formations ng and shut-in pressures es if gas to surface test, final geological well site	, whether shut-in palong with final ch	ressure reached s	static level, hydr	ostatic pressur	es, bottom hole
rill Stem Tests Taker		Yes X No		Log Formatio	n (Top), Depth a	and Datum	Sample
amples Sent to Geo	logical Survey	☐ Yes 🏻 No	Na	me	•	Тор	Datum
ores Taken lectric Log Run (Submit Copy)		☐ Yes					
st All E. Logs Run:				•			
Dual Ind Compensa	uction ted Neutron	Density					
		CASING Report all strings set-	_	New Used	on etc		
Purpose of String	Size Hole	Size Casing	Weight	Setting	Type of	# Sacjs	Type and Percent
existing Surface	Drilled	Set (In O.D.) 8-5/8**	Lbs. / Ft.	215 *	Cement	Used	Additives
		ADDITIONAL	CEMENTING / SQ	UEEZE RECORD			
Purpose: Perforate Protect Casing Plug Back TD Plug Off Zone	Depth Top Bottom	Type of Cement	#Sacks Used		Type and Po	ercent Additives	
Shots Per Foot		ON RECORD - Bridge Plug Footage of Each Interval Per			ire, Shot, Cement unt and Kind of Mai		Depth
	•						
JBING RECORD	Size	Set At	Packer At	Liner Run			,
to of Einst Day and 15			<u>. </u>		Yes No		
te of First, Resumerd P	roduction, SWD or Er	hr. Producing Meth	ood Flowing	g Pumping	☐ Gas Lift	Other	(Explain)
timated Production Per 24 Hours	Oil E	ibis. Gas i	Mcf Wate	er Bbls	Ga	as-Oil Ratio	Gravity
sposition of Gas	METHOD OF CO	DMPLETION ;		Production Interval			
Vented Sold	Used on Lease 1 ACO-18.)	Open Hole Other (Specify		Dually Comp.	Commingled		



SALES OFFICE:

105 S. Broadway Suite #420 Wichita KS 67202 (316) 262-3699 (316) 262-5799 FAX SALES & SERVICE OFFICE:

10244 NE Hiway 61 P.O. Box 8613 Pratt, KS 67124-8613 (316) 672-1201 (316) 672-5383 FAX

ACIDIZING · FRACTURING · CEMENTING

Total:

\$1,986.07

Bill to:	CMX, INC. Union Center Bldg. 150 N. Main, Suite 1026 Wichita, KS 67202	SEP 2 5 9 9 - 25 - 02 KCC MICHIEL		3005		067	der De 8/2/02
			\	<i>Leas</i> Whel	an	Wei OWW	01
AF	CustomerRep John Armbruster	Treater T/ Seba	Old W		urchase Order	Tern Net 3	
<i>D</i> .	<u>Description</u>	 	<u>UOM</u>	Quantity	Unit Price	Price	2
0203	60/40 POZ (COMMON)		SK	135	\$7.75	\$1,046.25	
321	CEMENT GEL		LB	465	\$0.25	\$116.25	
143	WOODEN CEMENT PL	UG, 8 5/8"	EA	1	\$85.00	\$85.00	
107	CEMENT SERVICE CHA	ARGE	SK.	135	\$1.50	\$202.50	(T)
100	HEAVY VEHICLE MILE	EAGE - 1 WAY	MI	30	\$3.00	\$90.00	(T)
E104	PROPPANT / BULK DE MILE, \$200 MIN	LIV SERVICES/TON	TM	176	\$1.25	\$220.00	(T)
R400	CEMENT PUMPER, PLU (Workover Unit)	JG & ABANDON	EA	1	\$650.00	\$650.00	(T)
					Sub Total:	\$2,410.00	
					Discount:	\$482.50	
				Discour	nt Sub Total:	\$1,927.50	
			Tax Rat	e: 6.30%	Taxes:	\$58.57	

(T) Taxable Item

● 15-007-20509-00-01 ● ORIGINAL

· O			•						•
Ĭ	7	INV	OKE NO.	Subje	ct to Correction		FIELD	ORDER	5067
Δ		Date	8.2-02	Lease WHE		טו	Well #	Legal_9-	315-11W
SER	VICES	Cust	lomer ID		Aebee		State K	Station	317
	14			Depth	Formation			Shoe Joint	10 1
C	<i>ν</i> Λ			Casing	Casing Depth	T	3835		EN WELL
R		 		Customer Repre	pontative RMBRUSTE	<u> </u>	Treater	T. SEBA	
Ε				JOHN A	<u>או צייטיטנייא</u>			113000	
AFE Number	<u> </u>	PO Number		Materials Received by	x Chil		1	/_ ;	1
Product	QUANTITY	MATERIAL	EQUIPMENT and S	1	UNIT PRICE	T AN	OUNT -		COUNTING AMOUNT
S-203	135 ski	60/43 Po		ERVICES USED	UNITERICE		OONI	CORRECTION	AMOUNT
C-321	A6516	CEMEINT				i			
F-143	1 EA	ubopen		85/8					
					<u> </u>				
					ļ				
			<u> </u>						
	<u> </u>								-
		<u></u> ,	<u></u> _						
						 			
	 		·						
	 		<u></u>						
							3,5		
	<u>_</u>					ļ 			
	 								
·.«-	 				<u> </u>				
	- 4					<u> </u>			
E-107	135 516	CEMENT	SERV. C	HAOGE					
E-100	30 ms			30	1				
E-104	176 TM	TONS	MILES						
R-400	LEA	EA. P.T.A	. PUMP CH	ARGE					
		DISWY		EGG:			3.30		<u> </u>
		+	TAXES			1,98	17.50		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0 0040	11 1/6 0 1	040 81 (**	PO) 672-1201 . F		070 000		
こいひんたき 川・春川	- DTICTIO 15	- 10 V - 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	のはませんできました何り	STATE SHOPE IS		レンコニンハイ	(マンス:マンン - ・	COTAL	

15-007-20509-00-01

ORIGINAL

TREATMENT REPORT

Pipe DATA PERFORATING DATA FLUID USED TREATMENT RESUME	G.	\				٦	Customer	ND O			T	ale			·
Lease West County Double County Double County Backer State Ks Type State Ks State						-	Sustomer	CMV			\dashv	g	- 3-02	•	
Field Depth Station ROST County County Barber Station Kry Kr	SER			ن		- -	.0030		A (2)		Le				
Trenchin A. NEW WELL PIPE DATA PERFORATING DATA FULID USED TREATMENT RESUME TREATMENT RESUME TREATMENT RESUME PATE PRESS ISIP FROM TO PROJUCT AND BY COLUMN Notice Volume From TO Fro				3500	<u>т</u>	<u>l</u>					a	ounty Ro	eher		KC
PIPE DATA PERFORATING DATA FLUID USED TREATMENT RESUME Consing Size Tobing Steve Shorter Depth Dopth From To Prophyly 6 2 Note: 5 Note: 5 Note: 5 Note: 10		<u> </u>							Formation	· -			Legal Descri	P150 2	
Dough Depth From To Pro Pod 61/4 16 2 Max 10 Max. Volume Volume From To Pad 61/4 16 2 Max 10 Max. Max Press Max Press Prom To Pad 61/4 16 2 Max 10 Max. Wall Connection Annaba Vol. From To From To Pouth Gas Volume Total Load Control Press Max Press Press To Pouth To Pouth To Gas Volume Total Load Control Press Max Press Max 11/4 26 38 70 Service Units Time Pressure Pressure Biblis Pumped Rate Service Log CALLED ONE TO Pressure Pressure Total Load ON Los WITEL'S F SA POTY MTG 15T Plug 600' 505/1 7.15 100 14.1	PIP		10W	1		TING DA	ATA	FI	LUID USED			T	REATMENT	RESUM	E
Dopth Opeth From To Pro PGU/42 B 2 Mac Shin. Volume Volume From To Pad 64 GC Min 10 Min. Mac Press Mex Press From To Pad 64 GC Min 10 Min. Mac Press Mex Press From To From To Plush One Volume To Shin. Plug Dopth Packer Dopth From To Plush One Volume Todal Load Customer Becomment of Plush Plush From To Plush One Volume Todal Load Customer Becomment of Plush Plush From To Plush One Volume Todal Load Customer Pressure Pressure Bible. Pumped Rais Service Log OS:30 ONLO WITH I SAPOTY MIT IST Plus 600' 605Ks 7:15 100 4 Plush Plush Found Solsks 4.3 (Dat 1959 4 2 Plush 240' 505Ks Marzi Fant Solsks Marzi Fant Solsks Marzi Fant Solsks 14.1 (Min 10 Min 10	Casing Size	Tubing	Size	Shots/F	1			130				RATE	PRESS	IS#P	
Volume Volume From To Pad 616 GBC Min 10 Min 10 Min Min Min Min 10 Min	Depth	Depth		Fmm		To	···	Pre Pad	40 Poz		Mex			5 Min.	
Max Press Mod Connection Annatus Vol. From To	Volume	Volume)	İ-				Pad 64	· liet		Min	_		10 Min.	
Well Connection Annalise Vol. From To Flush Ges Volume Ges Volume Total Load Proph Pecher Depth From To Flush Ges Volume Total Load Customer Bacycentrately Treater T. 568A Service Units Time Casing Tubing Pressure Bible. Pumped Rate Service Log CALLEO CA ON Low WITHER SONS 7. IS 100 14.1 While Flush Sons Sks 4.9 Bal. DISP Annalise Volume Total Load Annalise Pressure Total Load Annalise T	Max Press	Max Pre)GS	1	-						Avg	-		15 Min.	···
Customer Barresedatily From To Station Manager D. AUTRY Treater T. SEBA Service Units Time Pressure Pressure Blass. Pumped Rate Service Log 05:30 05:30 05:30 05:30 00.00 05:30 00.00 05:30 00.00	Well Connecti	on Annulus	Vol.								HHP	Used		Annulus	Pressure
1/4 26 38 70	Plug Depth	Packer	Depth	From		To		Flush			Ges	/olume		Total Los	d
1/4 26 38 70	Customer Rep	hw /ti	emt	neusi	FEE	Staf	ion Mana	Per D. A	uTRY			Treater 7	. 56B/	1	
Time Pressure Pressure Bob. Pumped Rule Service Log 05:30 CALLED OLD ONLOW WITHER'S FSAPOTY MTG IST Plug 600' BOSKS 7:15 100 14.1 MEX FRAMP SOSKS A.3 Quarant H20 Boal: DISP 2.222Plug 240' SOSKS MEZILAN PLANT H20 14.1 MEXIPANT BOSKS DOLE DISP 3.15 Z 320 Plug 40' 100KI Rump MILE Rump Wish CICL CMT TO SURFAGE W						-	Z 6								
06:30 ONLOW WITHLY & SAPOTY MTG 15T Plus 600' 505Ks Pure H 20 14.1	Time		4		Bbis. i	umped		Rate				Service	e Log		1
06:30 ONLOW WITHER SAPOTY MTG 15T Plug 600' 505Ks Plug 14.1 MILLE Plug 240' 505Ks MILLE Plug 240' 505Ks MILLE Plug 240' 505Ks MILLE Plug 240' 505Ks MILLE Plug 14.2 MIL	05:30								CALLE	o ou	\mathcal{T}				
15T Plug 600' 505Ks 7.15 100 4 Plug 1420 14.1 more i Plug 240' 505Ks 14.1 more i Plug 240' 505Ks more i Plug 240' 505Ks more i Plug 1426 14.1 more i Plug 1426 14.1 more i Plug 1426 155Ks 2.83 Rump More i Plug 155Ks 2.83 Rump More i Plug 155Ks 1	06:30								ONLOW	· w/7	rek	1 9 51	PETY	MIG	
14.1 mixi Pump SOSKS 4.3 Bal: DISP 4.2 2 Plug Z40' SOSKS mrzi Lu. Rumf H26 14.1 mrzi Pump SoSks 2 Dalt DISP 3.15 2 380 Plug 40' 103K1 2.83 Rump Mixi Pump DSLs CECC CMT TO SURTAGE V															
4.3 (Bal: DISP 2 PPHG 240' SOSKS mrzi Pun Pun/ H26 14.1 (Mrzi Pun/ 505KS 2.83) Bal: DISP 3.15 2.83) Rump Mixi Pun/ bosts cocc CMT TO Surface V 4.24 Phus R Hole 155Ks	7.1S	100	<u> </u>					9_						····	
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2									MEKF	Pump	50	SKS			
14.1 (mrzi Punt 1866) 14.1 (mrzi Punt 50sks 2 320 Plub 40' 10sks 2.83 Sump Mrxi Rumi Dsks CIEC CMT TO SURTAGE V 4.24 1 Plub R Hole 15sks			ļ		4.	<u> 9</u>			Bal +	DISP					
14.1 (mrzi Punt 1866) 14.1 (mrzi Punt 50sks 2 320 Plub 40' 10sks 2.83 Sump Mrxi Rumi Dsks CIEC CMT TO SURTAGE V 4.24 1 Plub R Hole 15sks			_						- 4120i		,				
14.1 (MIRI PUMP 505KS 2 3RP Plub 40' 105KI 2.83 \ Rump MIX & Rump WSLS CELL CMT TO SURFACE V 4.24 Plub R Hole 155KS								4_							
3.15 3.80 Plus 40' 105K1 2.83 Rump MERS PLUM DSLS CECC CMT TO SURFACE V 4.24 1 Plus R Hole 155Ks			ļ												
3.15 2.83 Rump MEX & PLIMP DSLS CECL CMT TO SURTAGE V 4.24 1 Plug R Hole 155Kg			-						MRIF	unal t	<u> 505</u>	<u>Es</u>			
2.83 S Rump MERS Rump DSLS CECL CMV TO SURTAGE V 4.24 1 Plug R Hole 150Kg			-				-	1	130CE 10	ISP		-			
2.83 S Rump MERS Rump DSLS CECL CMV TO SURTAGE V 4.24 1 Plug R Hole 150Kg	3		-				-	~	20001	1 1 1		И.			
4.24 1 Plug R Hole 150kg	2.13		-		2	タフ	-	\ \	Ja Plub	7 40	103	1 1 1			
4.24 1 Plug R Hole 150kg			 		٠	05	 								
			\vdash				+-	<u></u> .	CHEC C	M7 10	54	CTAU			
			 		4	24		1	PLA	Hali	≥ <u>1</u>	CNA			.
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			\dagger	-			-	`							
			 				+	•	1144 !	<u> </u>	<u> </u>	· 200			
8:30 SOB COMPLETE	8,30						 		<u> </u>	77.	73	Comp	IETE		
THANKS TODO										<u></u>	Ť	HANK	70	00	

10244 NE Hiway 61 • P.O. Box 8613 • Pratt, KS 67124-8613 • Phone (620) 672-1201 • Fax (620) 672-5383

Daily Drilling Report

ORIGINAL DRILLING REPORT

Well Name: Whelan #2 API Code: 15-007-20509-0001 Ref Well: W/2 SE NE 29 \ 31S \ 11W Lease Name: Whelan#2 Ref Loc: Location -// BARBER, KS County / State: BARBER, KS Field: Whelan Ext County: GL Level: 1625 Contractor: Duke Drilling Co. GL Level: KB Level: Operator: CMX, Inc. KB Level: 0 **Current Date** 02-Aug-02 Page 1 of 1

Daily Drilling Details Report

Date	Start Depth	Daily Remarks
7/31/2002	0	Move in and Rig up today. Will start tomorrow.
8/1/2002	0	Starting to drill on cement. Washed down to 3835'. Circulate for 2 hrs. Make short trip up into the surface pipe. Go back to bottom, circulate 2 hrs and add starch mud. TOH for logs. Rig up Reeves Wireline, ran Dual Induction and Compensated Neutron Density logs. Found that the Synderville interval was to shaley to be productive. Elected not to run repeat formation tester and ordered the well plugged and abandoned. Will send logs when received from Reeves.
8/2/2002		3835' laying down drill pipe to plug. 50 sx @ 600', 50 sx @ 240', 10 sx @ 40', 15 sx in RH, 10 sx in MH, Plugged down @ 8:30 AM.