

2 040172

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 0 7721069-00-00

NE/NE/NE, SEC. 16, T. 35 S, R. 5 W

4950 feet from N/S section line

330 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5230

Lease Name CD Williams Well # A-1

Operator: Petroleum Energy Inc.

County Harper

Name & Address 224 E. Douglas S.W. 350

Well Total Depth 5163 167.80 feet

Wichita Ks. 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 587

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Big Springs Drlg. License Number 5381

Address Wichita Ks.

Company to plug at: Hour: \_\_\_\_\_ Day: \_\_\_\_\_ Month: \_\_\_\_\_ Year: 19 \_\_\_\_\_

Plugging proposal received from Dave.

(company name) Big Springs Drlg. (phone) \_\_\_\_\_

were: 35 sx 1100

35 sx 640

15 sx 40 on Solid Bridge

10 sx RTT

RECEIVED  
STATE CORPORATION COMMISSION

MAR 06 1985

3-6-85  
CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Steve Suss (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 0630 Day: 2 Month: 3 Year: 19 85

ACTUAL PLUGGING REPORT Fill hole with mud and run drill pipe to 1100' and spot 35 sacks of cement. Pull drill pipe to 640' and spot 35 sacks of cement. Set a solid bridge at 40' and circulate with 15 sacks of cement. Circulate 10 sacks of cement thru drill pipe in the Rat hole.

Remarks: Howco 083110

(If additional description is necessary, use BACK of this form.)

I (did/did not) observe this plugging.

DATE 3-11-85

Signed Steve Suss (TECHNICIAN)

INV. NO. 7273

APR 10 1985