KANSAS STATE CORPORATION COMMISSION

STATE CORPORATION COMMISSION	
CONSERVATION DIVISION AGENT'S REPORT	
TO: j. P. Roberts Assistant Director 500 Insurance Building 212 North Market Wiching Kansas) In
File No County:	
Location: <u>SE. SIE</u> Sec. // Twp. 33 Rge. 8 (E) (W) 1.	ſ
Name of Field: Wildcat Total Depth: 5147'	
I have this date completed supervision of plugging of:	
Lease Name: Miller Well No. /	
Operator's Full Name: St. Silver + Sano	
Complete Address: Boy 921 - Wicheta Hansas	
Plugging Contractor Forbes Casing Pulling	
Address: Boy 221 Sheat Band Rano License No. 49	
OII WellD&A	
Other well as hereafter indicated:	
Was any delay in plugging operations caused by Conservation Division Agent	\$
YesNo	
If yes how long?Reason:	
Operation Completed: Hour 4100 Day 30 Month Jan Year 1962	
Operation Completed: Hour <u>HiOO</u> Day <u>30</u> Month Jan Year <u>1962</u> The above well was plugged as follows: 1. D. 5/117-1. P. 103-1-995 C. 11/2500021	
The above well was plugged as follows:	
The above well was plugged as follows: 1. D. 5147-8. P. 103/1-222 C. W. 1250/C/ 5/115146-2560-P.B. 5000-Job Pen 4890"	
The above well was plugged as follows: J. D. 5/47-8. P. 103/-222 C. W. 125 p/ C: 5/3' 5146-256 p/= P. B. 5000' Job Perf 4890' Bottom, sand to 4880 add 5 of cement.	
The above well was plugged as follows: (). D. 5/47'-S. P. 103/'-222 C. W. 125 p/C/ 5/3'' 5146'-256 p/= P. B. 5000'- Job Perf 4890' Bottom, sand to 4880 add 5 of common f. Pulled pipe, mud to 210' set R. B.	
The above well was plugged as follows: 1. D. 5/47-8. P. 103/-222 C. W. 125 A/C/ 5/3' 5146-256 A/= P. B. 5000 - Joh Park 4890' Bottom, sand to 4880 add 5 A/Cement. Pulled pife, mud to 210' set B. B. 10' R. B210-25 A/C	
The above well was plugged as follows: (). D. 5/47'-S. P. 103/'-222 C. W. 125 p/C/ 5/3'' 5146'-256 p/= P. B. 5000'- Job Perf 4890' Bottom, sand to 4880 add 5 of common f. Pulled pipe, mud to 210' set R. B.	
The above well was plugged as follows: 1. D. 5/47-8. P. 103/-222 C. W. 125 A/C/ 5/3' 5146-256 A/= P. B. 5000 - Joh Park 4890' Bottom, sand to 4880 add 5 A/Cement. Pulled pife, mud to 210' set B. B. 10' R. B210-25 A/C	
Signed: Harvel Moel's The above well was plugged as follows: 1. D. 5/47'-S. P. 103/"-222' C.W. 1250/C. 5/3" 5146'-2560/= P.B. 5000'- Jof Perf 4890' Bottom, sand to 4880 add 5 a coment. Pulled pife, mud to 210' set R. B. 10' R. B2210'- 25 a/C Signed: Fred W. Hample Conservation Division Agent	
The above well was plugged as follows: (). D. 5/47-S. P. 103/1-322 C. W. 1250/C1 5/15/5146-2560/E. P. B. 5000 - Dept 4890' Bottom, sand to 4880 add 5 a common. Pulled pife, mud to 310 set R. B. 10' R. B210-23 a/C R. B. 40-15 a/C Signed: Field Supervisor NVOICED	
The above well was plugged as follows: (). D. 5/47-S. P. 103/1-222 C. W. 125 pl C1 5/15/5146-256 pl P. B. 5000 Play 4890 Bottom, sand to 4880 add 5 alcoment. Pulled pife, mud to 210 set B. B. 10' R. B. 2210-23 sec R. B. 40-15 alc Signed: Field Supervisor [NVOICED]	