FÖRM CP-2/3 Rev.01-84

Tax	API NUMBER 15- Comp. 12-19-65
200 COLORADO DERBY BUILDING	C NW SE , SEC. 27 , T 30 S, R 12 W/SE N SE Corner of
WICHITA, KANSAS 67202	1980 feet from XWXXX section line W SE Corner of
TECHNICIAN'S PLUGGING REPORT	1980 W SE Corner of feet from MANNEX section line
Operator License # 9337	Lease Name Meairs Well # 1
Operator: Kansas Oil & Gas Corp.	
Nameå Address P.O.Box 148	Well Total Depth 4700 152.75 feet
Medicine Lodge, KS 67104	Conductor Pipe: Sizefeet
	Surface Casing: Size 8 5/8 feet 209
Abandoned Oll Well <u>y</u> Gas Well	Input Well D&A
Other well as hereinafter indicated	
lugging Contractor Clarke Corporation	License Number 5105
Address Box 187, Medicine Lodge, KS 671	.04
Company to plug at: Hour: noon Day:	19 Month: September Year:19 84
Plugging proposal received from	
•	(phone) 316-886-5665
were: 5 1/2" set at 4699' PBTD 3810'	
1st plug sand back to 3610 and dump 5 s	
2nd plug pump 3 sx hulls, 10 sx gel, 50 100 sx cement.	sx cement, 10 sx ger, 1 sack nuris and
100 SA Cement.	
	T. IV.
Plugging Pro	oposal Received by J. H. Metz (TECHNICIAN)
Plugging Operations attended by Agent?:	All X Part None
	: 19 Month: September Year:19 84
	at 4699' PBTD 3810' Perfs at 3663-3669'
	1 5 sx cement on top of sand through bailer, 50 sx cement, 10 sx gel, 1 sack hulls and 100 sx
	Profive)
cement.	STATE CONTROLLED COMMISS
comette.	7 2 2 7 17777
Cometit,	9-24-84 cfp 9-4 1984
) psi SFP 2 4 1984
Maximum pressure 700 psi and shut in 500	ONSERVATION Michital Kansas
Maximum pressure 700 psi and shut in 500 Remarks: Used 60/40 Pozmix 2% gel 3%cc (If additional description) psi SFP 2 4 1984 CONSERVATION DEVISION
Maximum pressure 700 psi and shut in 500 Remarks: Used 60/40 Pozmix 2% gel 3%cc (If additional description I Nd Va O description	ONSERVATION DIVISION ONSERVATION DIVISION Michila, Kansas Is necessary, use BACK of this form.)
Maximum pressure 700 psi and shut in 500 Remarks: Used 60/40 Pozmix 2% gel 3%cc (If additional description	ONSERVATION Michital Kansas