

1 010165

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-007-21,497-00-00

C NW NW, SEC. 22, T 30 S, R 12 W/8

4620 feet from S section line

4620 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5087

Lease Name House Well # 1-A

Operator: Texas Energies, Inc.

County Barber 146.58

Name & Address P.O. Box 946

Well Total Depth 4510 feet

Pratt, KS 67124

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 330

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Wheatstate Oilfield Services License Number 5149

Address P.O. Box 329 Pratt, KS 67124

Company to plug at: Hour: 10:50 a.m. Day: 19 Month: 8 Year: 1986

Plugging proposal received from Ted Moff

(company name) Wheatstate (phone) 316-762-7514

were: 4 1/2" at 1025' Perfs at 3472-3482 Elevation 1756' GL

1st plug pump 25 sx of common cement followed by 30 bbls. mud.

2nd plug squeeze with 3 sx hulls and 80 sx of Halco lite cement.

Plugging Proposal Received by Jack Luthie  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11:10 a.m. Day: 19 Month: 8 Year: 1986

ACTUAL PLUGGING REPORT 1st plug pumped 25 sx of common cement followed by 30 bbls. mud.

2nd plug squeezed with 3 sx hulls and 80 sx of Halco lite cement.

Maximum pressure 400 psi and shut in 300 psi.

AUG 22  
8-22-86

Remarks: Recovered 1025' 4 1/2" casing. Used Halco Lite Cement by Halliburton.  
(If additional description is necessary, use BACK of this form.)

INVOICED (do not check) observe this plugging.

Signed Jack Luthie  
(TECHNICIAN)

DATE AUG 22 1986

INV. NO. 14811