

15-007-10030-0000

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

OR

FORMATION PLUGGING RECORD

Strike out upper line
when reporting plug-
ging off formations.

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

Barber County. Sec. 29 Twp 31 S Rge. 11 (E) W (W)

Location as "NE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ " or footage from lines Center NW $\frac{1}{2}$ NW $\frac{1}{4}$

Lease Owner C.L. McMahon

Lease Name Frank Whelan Well No. 1

Office Address 1603 National Bank of Tulsa Bldg, Tulsa Okla.

Character of Well (Completed as Oil, Gas or Dry Hole) dry hole

Date, well completed Sept. 15 1940

Application for plugging filed Oct. 3 1940

Application for plugging approved Oct. 3 1940

Plugging Commenced ~~WKY~~ Sept. 30 1940

Plugging Completed Oct. 7 1940

Reason for abandonment of well or producing formation dry hole

If a producing well is abandoned, date of last production 193

Was permission obtained from the Conservation Division or its agents before plugging was commenced? yes

Name of Conservation Agent who supervised plugging of this well C.T. Alexander

Producing formation chat Depth to top ~~4345~~ Bottom 4400 Total Depth of Well 4400 Feet.

Show depth and thickness of all water, oil and gas formations. 4345


OIL, GAS OR WATER RECORDS CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
		top	4347	5 $\frac{1}{8}$ OD	4347	2939' 7 $\frac{3}{4}$

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from mud 4400 feet to 4341 feet for each plug set. put in by Halliburton. Wood plug set at 4341 and 10 feet of rock was put on top of plug then cemented to 4293 then mud dumped with bailer to 136' and wooden plug set then 10 feet of rock was put on top of plug then 16 feet of cement was dumped on top of rock then mud to 14 feet and cement to 8 feet then filled to surface with dirt.

pd
10/4/40
Pa, i

29 31 11W
118 3



(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to C.D. McMahon
Address 1603 National Bank of Tulsa Bldg., Tulsa, Okla.

STATE OF Kansas, COUNTY OF Barber, ss.

P. J. Nealon (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) P. J. Nealon

521 S. Jeff. Okmulgee, Okla.
(Address)

SUBSCRIBED AND SWORN to before me this 8th day of October 1940.

My commission expires May 23, 1941

Notary Public

Well started

Aug. 18-1940

Completed Sept 15-1940


OLSON DRILLING COMPANY
 INCORPORATED
 WRIGHT BUILDING
 TULSA, OKLAHOMA

Well #1

Sec 29-31-11

Cor. NW 1/4 - NW 1/4

100'	red rock + shale
100 - 355	red rock + shale
355 - 440	red shale + shells
440 - 850	"shale" lime shells
850 - 1008	"shale" lime shells
1008 - 1250	"shale" lime shells
1210 - 1494	silt + shale - shells
1494 - 1654	shale + lime shells
1654 - 1891	shale - lime
1891 - 2086	lime
2086 - 2236	lime
2236 - 2281	limestone
2281 - 2397	shale + lime
2397 - 2422	shale + lime
2422 - 2699	"sandy" shale
2699 - 2784	shale
2784 - 2832	shale + lime shells
2832 - 2914	lime
2914 - 3014	lime
3014 - 3073	broken lime
3073 - 3135	hard lime
3135 - 3211	hard lime
3211 - 3275	shale - lime shells
3275 - 3352	shale - lime
3352 - 3548	shale - lime
3548 - 3722	sand + shale
3722 - 3763	shale
3763 - 3764	lime
3764 - 3875	lime



29 31 114
 118 3

OLSON DRILLING COMPANY
INCORPORATED
WRIGHT BUILDING
TULSA, OKLAHOMA

3875 - 3944 lime
 3944 - 4033 lime
 4033 - 4124 lime + chert
 4124 - 4145 lime + chert
 4145 - 4295 lime + shale
 4295 - 4342 lime + shale
 4342 - 4349 chat
 4349 - 4360 chat - show of gas
 4360 - 4369 chat - show of oil
 4369 - 4378 hard chat no increase in oil or gas
 4378 - 4400 hard chat no increase in oil or gas
 put in 50 quarts of glycerine top of shot 4368
 tamped shot with 1/2 yard gravel
 cleaned out to bottom no increase in oil or gas
 hole making water

29 31 110
118 3

10-9-40
 OCT 9 1940
 STATE GEOLOGICAL SURVEY
 CONSERVATION