## KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| _ :   | :<br>en Flov<br>liverab      |   |  |  | Test<br>08/2   | Date                        | :                                | ictic           | ons on Rev   | ∕erse Side                           | ÁPI  | No. 15<br>077-20792-(       | 00-01                |  |                                      |   |  |
|---|------------------------------|---|--|--|--|-----------------------------|----------------------------------|-----------------|--|--------------------------------------|--|-----------------------------|----------------------|--|--------------------------------------|---|--|
| Company<br>WOOLS  |                              | PER   | ATING CO   | MPANY, LL  |  | .0/13                       | •                                |                 | Lease<br>GAMMII  | <br>LL                               | 10-  | 011-20192-                  | 70-01                | 1                                      | Well Nu                              | mber  |  |
| County Location HARPER C NW NW                              |                              |   |  |  | Sect<br>27   | Section<br>27               |                                  |                 | TWP<br>32 SW   |                                      | RNG (E/W)<br>8W  |                             |                      | Acres Attributed                       |                                      |   |  |
| Field<br>SULLIVAN EAST                                      |                              |   |  |  | Rese<br>STA  |                             | KER                              |                 |  |                                      | Gas Gathering Connectio  |                             |                      | ATHERIN                                | <br>G                                |   |  |
| Completion Date 4/17/82                                     |                              |   |  |  | Plug<br>370  |                             | Total De                         | pth             |  | Packer Set at NONE                   |  |                             | · · ···              | <del></del>                            |                                      |   |  |
| Casing S<br>4.500   | asing Size Weight .500 10.50 |   |  |  |  | Internal Diameter<br>4.052  |                                  |                 | Set at<br>3935   |                                      | Perforations<br>3627   |                             |                      | To<br>3662                             |                                      |   |  |
| <del>-</del>  |                              |   | Weigh<br>4.70                                      | ıt   |  | Internal Diameter<br>1.995  |                                  |                 | Set at<br>3692   |                                      | Perforations<br>OPEN   |                             |                      | То                                     |                                      |   |  |
| Type Completion (Describe) SINGLE                           |                              |   |  |  | Туре   |                             | d Producti                       | ion             | 3092   | Pump Unit or Travel PUMPING          |  |                             | ng Plunger? Yes / No |  |                                      |   |  |
| Producing Thru (Annulus / Tubing) ANNULUS                   |                              |   |  |  |  | % Carbon Dioxide            |                                  |                 |  |                                      | % Nitrog   |                             |                      | Gas Gravity - G                        |                                      |   |  |
| Vertical D  |                              | l)  |  |  |  |                             | Pre                              | 9 <b>\$</b> \$1 | ure Taps   |                                      |  | <del></del>                 |                      | (Meter                                 | Run) (P                              | rover) Size   |  |
| 3650<br>Pressure  | Buildu                       | n'  | Shut in08/   | 20/13  | 20 a   | at .                        |                                  |                 | (AM) (PM)  | Taken 08                             | 3/21/13  | 20                          |                      | nt                                     |                                      | ΔΜ\ (PM)  |  |
| Well on L   |                              |   |  |  |  |                             |                                  |                 |  |                                      |  |                             |                      |  |                                      |   |  |
|   |                              |   |  |  |  |                             | OBSERV                           | /ED             | SURFACE  | E DATA                               | · · · · · · · · · · · · · · · · · · ·  |                             | Durati               | on of Shut-                            | in                                   | Hours   |  |
| Static /<br>Dynamic<br>Property                             | mic Size                     |   | Circle one:<br>Meter<br>Prover Pressu<br>psig (Pm) | Pressure Differentia in Inches H <sub>s</sub>  | Tempera  | Flowing<br>Temperature<br>t |                                  | te _            | Casing Wellhead Pressure (P <sub>w</sub> ) or (P <sub>1</sub> ) or (P <sub>c</sub> ) |                                      | Tubing Wellhead Pressure (P <sub>w</sub> ) or (P <sub>t</sub> ) or (P <sub>c</sub> ) psig psia |                             | Duration<br>(Hours)  |  | Liquid Produced<br>(Barrels)         |   |  |
| Shut-In   |                              | P-97 7  |  |  |  |                             |                                  |                 | psig<br>55   | psia                                 | ·60  | psia                        | 24                   |  |                                      |   |  |
| Flow  |                              |   |  |  |  |                             |                                  |                 |  |                                      |  |                             |                      |  |                                      |   |  |
|   | <u> </u>                     |   |  | •  |  |                             | FLOW ST                          | TRE             | AM ATTR  | IBUTES                               | <u>_</u>   |                             | -                    |  |                                      |   |  |
| Plate Coeffiecient (F <sub>b</sub> ) (F <sub>p</sub> ) Mcfd |                              | Circle one:<br>Meter or<br>Prover Pressure<br>psia              |  |  | Futoncies  |                             | avity<br>actor<br>F <sub>g</sub> |                 | Flowing<br>imperature<br>Factor<br>F <sub>11</sub>                                   | Fa                                   | iation<br>etor<br>:<br>pv  | Metered Flow<br>R<br>(Mcfd) |                      | GOR<br>(Cubic Fe<br>Barrel)            |                                      | Flowing<br>Fluid<br>Gravity<br>G <sub>m</sub>               |  |
|   |                              |   |  | 1.0  |  |                             |                                  |                 |  |                                      |  |                             |                      |  |                                      |   |  |
| (P <sub>c</sub> ) <sup>2</sup> =                            |                              | _:  | (P <sub>w</sub> ) <sup>2</sup> =                   | ::   | •  | 1 FL(<br>P <sub>a</sub> = . | OW) (DEL                         | IVE<br>_%       | RABILITY)<br>(P  | ) CALCUL<br><sup>)</sup> c - 14.4) + |  | :                           |                      | (P <sub>a</sub> )<br>(P <sub>d</sub> ) | <sup>2</sup> = 0.2<br><sup>2</sup> = | 07  |  |
| $(P_c)^2 - (P_a)^2$<br>or<br>$(P_c)^2 - (P_d)^2$            |                              | (P <sub>0</sub> ) <sup>2</sup> - (P <sub>w</sub> ) <sup>2</sup> |  | Choose formula 1 of  1. $P_c^2 - P_a^2$ 2. $P_c^2 - P_d^2$ divided by: $P_c^2 - F_d^2$ | 1. P <sub>c</sub> <sup>2</sup> -P <sub>a</sub> <sup>2</sup> LOG of formula 2. P <sub>c</sub> <sup>2</sup> -P <sub>d</sub> <sup>2</sup> 1. or 2. and divide |                             |                                  |                 | Backpressure Curve Slope = "n"or Assigned Standard Slope                             |                                      | n v 106  |                             | ,                    | Antilog                                |                                      | Open Flow<br>Deliverability<br>Equals R x Antilog<br>(Mcfd) |  |
|   |                              |   |  |  |  |                             |                                  |                 |  |                                      |  |                             |                      |  |                                      |   |  |
| Open Flow Mcfd @ 14.65                                      |                              |   |  |  | 4.65 psia  | psia [                      |                                  |                 |  | ility                                |  | Mcfd @ 14.65 p              |                      |  |                                      | sia   |  |
|   |                              | _   | -  | n behalf of th<br>aid report is tr   | -  | -                           |                                  |                 | •  |                                      |  | e above repo                | rt and               | that he ha                             |                                      | ledge of 20 <u>13</u> .                                     |  |
| ine recis s   | ıaı⊕0 (I                     | HELBI   | n, and that sa                                     | aiu report is tr   | ue and co  | ∍i (⊕C)                     | . ⊏X&CUl€                        | eu (            | nis (Tie   |                                      | day or <u> </u>  |                             | Dan                  |  |                                      |   |  |
|   |                              |   | Witness (  | if any)  |  |                             |                                  |                 | _  | <u>-</u>                             |  |                             | ompany               |  | KCC                                  | WICH  |  |
|   |                              |   | For Comm   | nission  |  |                             |                                  |                 | _  |                                      |  | Che                         | cked by              |  | DEC                                  | 18 20   |  |

**RECEIVED** 

| exempt status ur<br>and that the fore<br>correct to the be<br>of equipment ins<br>I hereby req | der penalty of perjury under the laws of the state of Kansas that I am authorized to request oder Rule K.A.R. 82-3-304 on behalf of the operator WOOLSEY OPERATING CO., LLC egoing pressure information and statements contained on this application form are true and st of my knowledge and belief based upon available production summaries and lease records tallation and/or upon type of completion or upon use being made of the gas well herein named. Usest a one-year exemption from open flow testing for the GAMMILL #1 |
|--|---|
| (Chec  | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No is not capable of producing at a daily rate in excess of 250 mcf/D ee to supply to the best of my ability any and all supporting documents deemed by Commission by to corroborate this claim for exemption from testing.   |
| Date: 12/09/13   | Signature: <u>Um l Hallayta</u> Title: FIELD MGR.   |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.