KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| Type Test | t: | | | | (| See Instruct | ions on Revi | erse Side |) | | | | |
|--|---|-------|---|--|---|---|---|--|--|---|-------------------------------------|---|--|
| Ор | en Flo | w | | | Test Date | | | | ADI 4 | .I_ 45 | | | : |
| De | liverab | ilty | | | 7/3/13 | | | | | No. 15 77-21828-0 | 0-00 | | • |
| Company MTM Pe | | m, le | nc. | | | -0 | Lease Maloney | M | | +====================================== | 2 | Well Nur | mber |
| County Location HP W2 SW SE | | | | Section 6 | | | | RNG (E/W) 7W | | ē | Acres Attributed | | |
| Field Washbon | | | Reservoir Mississippi | | | ······································ | Gas Gathering Connection West Wichita Gas Gathering | | | | , | | |
| Completic 5/10/201 | | е | 1-1 | | Plug Bad 4460 | k Total Dept | h | | Packer Se | et at | | m = 1 d = 1 | |
| Casing S 4-1/2 | ize | | Weigh 10.5 | ĺ | Internal Diameter 3.927 | | Set at 4500 | | Perforations 4402 | | то 4406 | | ! |
| Tubing Size Weight 2.375 4.7 | | | | Internal Diameter 1.995 | | Set at 4445 | | Perforations 4431 | | To 4434 | , | | |
| Type Con Single | Type Completion (Describe) Single | | | | * * | d Production Gas/Oil | Pump Un Pumpi | | | Plunger? Yes | / No | 1 | |
| Producing Tubing | g Thru | (Anr | nulus / Tubing |)) | % C | arbon Dioxi | de | | % Nitroge | | Gas G | ravity - G | · , |
| Vertical D | Depth(F | 1) | | | | | sure Taps | | | | (Meter | Run) (Pr | over) Size |
| Pressure | Buildu | p: | Shut in7/2 | 2 | 0 13 at 9: | Flang :45 | | Taken 7/ | 3 | 20 | 13 _{at} 9:45 | | AM) (PM) |
| Well on L | Well on Line: | | Started 20 | | | | | | | | | | |
| | | | | | | OBSERVE | D SURFACE | DATA | • | | Duration of Shut | | Hours |
| Static / Dynamic Property | Orifi Siz (inch | е | Circle one: Meter Prover Pressu psig (Pm) | Pressure Differential in Inches H ₀ 0 | e Flowing Temperature t Tubing Wellhead Pressure (P _*) or (P ₁) or (P _c) Tubing Wellhead Pressure (P _*) or (P ₁) or (P _c) | | Duration (Hours) | (Hours) (Barrels) | | | | | |
| Shut-In | | | | | , | | 286 | psia | psig | psia | ! | , | |
| Flow | | | | | | | | - | | | | <u> </u> | |
| | - 1 | | | | | FLOW STR | EAM ATTRI | BUTES | | | | | |
| Coeffied (F _b) (F | Plate Coefficeient (F _b) (F _p) Mcfd | | Circle one: Meter or over Pressure psia | Press Extension P _m xh | Gravity Factor F _g | | lemperature F | | viation Metered Flow factor R F _{pv} (Mcfd) | | y GOR (Cubic F Barrel | eet/ | Flowing Fluid Gravity G _m |
| | | | <u> </u> | | (OPEN FL | OW) (DELIV | ERABILITY) | CALCUL | ATIONS | | (5) | \2 0.0 | i |
| (P _c) ² = | | _:_ | (P _w)² ≃ | : Channel from Ja 1 2 | P ₄ = | | , | - 14.4) + | | ; ; | |) ² = 0.20) ² = | |
| (P _e) ² - (F or (P _e) ² - (F | ŀ | (F | (P _w) ² - (P _w) ² | Choose formula 1 or 2 1. $P_c^2 - P_a^2$ 2. $P_c^2 - P_d^2$ divided by: $P_c^2 - P_a^2$ | LOG of formula 1, of 2, and divide | P,2-P,2 | Siop | sure Curve e = "n" or igned rd Slope | | og [| Antilog | Deli Equals | en Flow verability Fl x Antilog Mcfd) |
| | | | | | - | • | | | | | | | ı |
| Open Flo | | | | 14a64 @ 4.6 | GE nois | | Defineshi | Ca. | | | NA-11 @ 44 05 | | , |
| | | ianeo | d authority or | Mcfd @ 14. | · · · · · · · · · · · · · · · · · · · | tates that h | Deliverabi | | n make th | | Mcfd @ 14.65 ps rt and that he h | | ladge of |
| | | | | id report is true | | | | | day of De | | 1 | | 20 13 |
| | | | Witness (i | any) | | -KC | C WICI | ARK | /ac | For C | Company | B | |
| · | | | For Comm | | | | C 1 1 20 | | | | | | |
| | | | , 5, 50am | | | חבו | ا2 ۱۱ د | 113 | | Chec | ked by | • | 1 |

RECEIVED

| _ | is not capable of producing at a daily rate in excess of 250 mcf/D ee to supply to the best of my ability any and all supporting documents deemed by Commission ry to corroborate this claim for exemption from testing. |
|---|--|
| (Chec | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No |
| and that the fore correct to the bes of equipment inst I hereby requ | der Rule K.A.R. 82-3-304 on behalf of the operator MTM Petroleum, Inc. going pressure information and statements contained on this application form are true and it of my knowledge and belief based upon available production summaries and lease records allation and/or upon type of completion or upon use being made of the gas well herein named. est a one-year exemption from open flow testing for the Maloney M #2 rounds that said well: |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.

DEC 1 1 2013 RECEIVED