p. 20 .

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

Type Test	t:			((See Instructions on Reverse Side)								
Op	en Flow			Took Date:									
Deliverabilty					Test Date: 11/14/13				API No. 15 , NA 15-007-01469-0001				
Company Oil Prod		nc.of Kansas			Lease Sutton Estate			1			Well Number		
County Location Barber NESW				Section 30		TWP 34S			RNG (E/W) 13W		Acres Attr	buted	
Field Hetna				Reservoii Mississi				Gas Gath	ering Conne	ection			
Completion Date				Plug Back Total Depth 4825				Packer Sonone	et at		•		
Casing Size Weight 5.5			nt	internal [Diameter	Set at 4851		Perforations 4792		To 4812			
Tubing Size Weight 2.375			nt	Internal [Diameter	Set 482		Perforations		То			
Type Completion (Describe) single				Type Flui oil/sw	d Production	n			t or Traveling mp unit	Plunger? Yes	/ No		
Producing Thru (Annulus / Tubing) annulus				% C	% Carbon Dioxide			% Nitroge	en	Gas Gr	Gas Gravity - G		
Vertical D					Pres	sure Taps			•	(Meter	Run) (Prov	er) Size	
Pressure	Buildup:	Shut in 11	/13 2	0_13 at_1	1:15 am	(AM) (PM)	Taken_1	1/14	20	13 at 11:15	am_ (AM	1) (PM)	
Well on Line: Started 20				at (AM) (F			Taken		20	at	(AM) (PM)		
					OBSERVE	D SURFAC	E DATA			Duration of Shut-	in 24	Hours	
Static / Dynamic Property	Orifice Size (inches) Circle ane: Meter Pressure Differential Pressure Differential Pressure Differential Pressure Differential Inches H ₂ 0		Flowing Well Head Temperature t t		Casing Wellhead Pressure (P _w) or (P _t) or (P _c)		Tubing Wellhead Pressure (P _w) or (P _t) or (P _c)		Duration (Hours)		Liquid Produced (Barrels)		
Shut-In		poig (i iii)	monds rigo			85.6	100.0	psig	psia	24			
Flow											<u> </u>		
	-				FLOW STR	REAM ATTE	RIBUTES	· _T					
Plate Coeffiecient (F _b) (F _p) Mcfd		Circle one: Meter ot Prover Pressure psia	Press Extension ✓ P _m xh	Grav Fac F	tor	Temperature F		viation Metered Flow actor R F _{pv} (Mcfd)		GOR (Cubic Fe Barrel)	eet/	Flowing Fluid Gravity G _m	
:			<u> </u>	<u> </u>									
(P _c) ² =		(P _w) ² =	=:	(OPEN FL	OW) (DELIV 		/) CALCUL P _c - 14.4) +		:	(P _a) (P _d)) ² = 0.207) ² =		
$(P_c)^2 - (P_a)^2$ or $(P_c)^2 - (P_d)^2$		(P _c) ² - (P _w) ² (P _c) ² - (P _w) ² 2. P _c ² - P _d ² divided by: P _c ² - P _w ²		LOG of formula 1. or 2.		Backpressure Curvi Slope = "n" or Assigned Standard Slope		n x LOG		Antilog	Deliver Equals R	Open Flow Deliverability Equals R x Antilog (Mcfd)	
Open Flo	Open Flow Mcfd @ 14.65 psia						Deliverability				Mcfd @ 14.65 psia		
		ned authority of			states that h			o make th		rt and that he ha		lge of	
	_	-	aid report is true					17	ovember		C WI		
	<u> </u>						/8	they I	llen				
		Witness	(II any)				ar	14,10	For C	Company	EC 18	2013	

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under OBSERVED SURFACE DATA. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption IS denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be KCC WICHITA signed and dated on the front side as though it was a verified report of annual test results.