1 040357	11-21
To: STATE CORPORATION COMMISSION	API NUMBER 15-007-21,340
CONSERVATION DIVISION - PLUGGING SECTI	ON SW NE SW, SEC. 35, T 34 S, R 12 W/K
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	1650 feet from S section line
TECHNICIAN'S PLUGGING REPORT	3630 feet from E section line
Operator License # 5552	Lease Name Morton "A" Well # 6
Operator: Gore Oil Company	
Name& 125 North Market, Suite 1750	
Wichita, KS 67202	
	Surface Casing: Size 8 5/8 feet 311
Abandoned Oli Weit X Gas Weil	Input Well D&A
Other well as hereinafter indicated	
Plugging Contractor Clarke Corporation	
Address P.O. Box 187, Medicine Lodge,	K5 07104
Company to plug at: Hour: 12 p.m. Da	y: 21 Month: 11 Year: 19 89
lugging proposal received from Scot	t Scheuerman
(company name) Gore Oil Company	(phone) 316-263-3535
were: 4½" at 4849' PBTD 4832' Perfs	at 4764-4774
	4 sx cement on top of sand through bailer,
•	50 sx cement, 10 sx gel, 1 sx hulls, release 8-5/8"
wiper plug and pump 100 sx cement.	
	NOV 2 8 1989
Plugging	Proposal Received by Steve Pfeifer (TECHNICHAN): Kanses
Divising Operations attended by Agent?	: All X Part None
Operations Completed: Hour: $12:30 \text{ p.mb}$	
CTUAL PLUGGING REPORT 1st plug sanded	d back to 4710' and dumped 4 sx cement on top of
sand bridge with bailer,	
	ipe with 400 lbs. hulls, 10 sx gel, 50 sx cement,
10 sx gel, 100 lbs. hulls, released 8	5/8" wiper plug and pumped 100 sx cement.
Maximum pressure 450 psi and shut in 1	l50 psi.
Remarks. Used 60/40 Pozmix 6% gel by B	3.J. Titan. Recovered 3550' of $4\frac{1}{2}$ " casing.
(if additional description	g. A.
(1) O DOSE OBSERVE this pluggin	9.
12 1 89	g.

FORM CP-2/3 Rev.01-84