## Kansas Corporation Commission One Point Stabilized Open Flow or Deliverability Test

| ype Test:   |   |   |         |           |  | (5   | See In              | structi   | ions o                   | n Rev                                  | erse S   | Side)                       |  |          |                                   |   |                      |  |   |  |
|---|---|---|---------|-----------|--|--|---------------------|---|--------------------------|--|--|-----------------------------|--|----------|-----------------------------------|---|----------------------|--|---|--|
| Open Flow Deliverability Test D                                     |   |   |         |           | Test Date                                | nate: 11/01/2013                                   |                     |   |                          |  |  |                             | API No.  |          |                                   |   | 15187211380000       |  |   |  |
| Company<br>OXY USA  | Inc   |   |         |           |  |  |                     | Lease<br>HERF                                       |                          | 4-G2                                   | 7-30-  | 40                          |  | _        |                                   |   |                      | Well   | l Number  |  |
| ounty Location tanton NE SW SW NE                                   |   |   |         |           |  | Section<br>27                                      |                     |   | TWP<br>30\$              |  |  |                             | RNG (E/W)<br>40W                               |          |                                   |   | Acres Attributed 640 |  |   |  |
| ield<br>HORE  |   |   |         |           |  | Reservoir<br>WABAUNSEE                             |                     |   |                          |  |  |                             | Gas Gathering Connec                           |          |                                   | nectio  | 'n                   |  |   |  |
| ompletion<br>2/02/200   |   |   |         |           |  | Plug Back<br><b>3,350</b> '                        | k Tota              | l Dept  | th                       |  |  |                             | Packe  | r Set at |                                   |   |                      | •  | • "   |  |
| asing Size  |   |   |         |           |  | Internal Diameter<br>4.950"                        |                     |   |                          | Set at<br><b>3,425</b> '               |  |                             | Perforations<br>2,939'                         |          |                                   | To<br><b>2,961</b> '                            |                      |  |   |  |
| ubing Size  | Weight<br>4.7#  |   |         |           |  | Internal Diameter<br>1.995"                        |                     |   | Set at<br><b>4,066</b> ' |  |  |                             | Perforations                                   |          |                                   | То  |                      |  |   |  |
| pe Comp   |   | escribe)  |         |           |  | Type Fluid   | d Proc              | luction   | n                        | <u> </u>                               |  |                             | Pump   | Unit or  |                                   |   | unger?               |  | Yes / No  |  |
| roducing 1  | Thru (Ann<br>Tubing   |   | ıbing)  |           |  | %  | Carbo               | on Dio  | xide                     |  |  |                             | % Nitr   | ogen     |                                   | <u></u>   | Gas G                | ravity   | - Gg  |  |
| ertical Der   |   |   |         |           |  |  | ı                   |   | ure Ta                   | aps                                    |  |                             |  |          |                                   |   | (Meter               | •  | (Prover) Size   |  |
| essure Bu   | uildup:   | Shut in   |         | 10/3      | 1  | 20 13  | at                  | 9:00  |                          |  | T  | aken                        |  | 11/01    |                                   | 20 <b>13</b>                                    | at                   | 9:0  | 0   |  |
| ell on Line   | e:  | Shut in   |         |           |  | 20   | at                  |   |                          |  | Т  | aken                        |  |          |                                   | 20  | at                   |  | _   |  |
| -   |   |   |         |           |  |  | ОВ                  | SERV  | ED S                     | URFA                                   | CE D   | ATA                         |  |          | Dura                              | tion of   | Shut-in              |  | 24 Hours  |  |
| Static /<br>Dynamic<br>Property<br>Shut-In                          | Oritice<br>Size<br>(inches)   | ce Meter Differ<br>Prover Pressure                          |         |           | Pressuri<br>Differenti<br>in<br>Inches H | ential Flowing<br>Temperature                      |                     |   |                          | (P <sub>w</sub> )<br>psig              | Casing Wellhead Pressure (P <sub>w</sub> ) or (P <sub>i</sub> ) or (P <sub>o</sub> ) psig psia  172.0 186. |                             | (P <sub>w</sub> ) or (P <sub>i</sub> ) or psig |          | d Press<br>(P <sub>I</sub> ) or ( | essure or (P <sub>c</sub> ) Duratio psia (Hours |                      | urs)   | Liquid Produ<br>(Barrels)                                   |  |
| Flow  |   | <del></del>   |         | Т         |  |  |                     | 172.0 186   |                          | 1.4                                    |  | -                           | 24   |          | :4                                |   |                      |  |   |  |
| TIOW  |   | 1   |         |           |  |  |                     | W OT  | DEA                      |  | - DIDI   | TEO                         |  |          | <u> </u>                          |   | <u> </u>             |  | _L  |  |
| Plate<br>Coefficient<br>(F <sub>b</sub> ) (F <sub>p</sub> )<br>Mcfd | Coefficient Meter or Exten<br>(F <sub>b</sub> ) (F <sub>p</sub> ) Prover Pressure |   |         | nsion     | Gravity                                  |  |                     | Flowing<br>Temperature<br>Factor<br>F <sub>tt</sub> |                          | Deviation<br>Factor<br>F <sub>pr</sub> |  | Metered Flow<br>R<br>(Mcfd) |  | ,        | GOR<br>(Cubic Feet/Barrel)        |   | el)                  | Flowing<br>Fluid<br>Gravity<br>G <sub>m</sub>                    |   |  |
| c) <sup>2</sup> =   | :   | (P,   |         | 0.0       | :  | (OPEN FI   | LOW)                | (DEL  | IVER/                    |  | •  | ALCU<br>() + 14             |  | INS      |                                   |   |                      | (P <sub>a</sub> ) <sup>2</sup><br>(P <sub>d</sub> ) <sup>2</sup> | = 0.207   |  |
| $(P_c)^2 - (P_a)^2$<br>or<br>$(P_c)^2 - (P_d)^2$                    | (P <sub>c</sub> )   | $(P_c)^2 - (P_w)^2$ Choose For 1. $P_c$ 2. $P_c$ divided by |         |           | 2<br>d                                   | LOG of<br>formula<br>1. or 2.<br>and divide<br>by: | P <sub>c</sub> ²    | ,2 · P,2  |                          | Backpressure Curve Slope = "n"         |  |                             | nxLOG  |          |                                   | Antifog   |                      |  | Open Flow<br>Deliverability<br>Equals R x Antilog<br>(Mcfd) |  |
|   |   |   |         |           |  |  |                     |   |                          |  |  |                             |  |          | $\dashv$                          |   |                      | $\dashv$   | -   |  |
| en Flow   |   | 0   | 1       | Mcfc      | 1 @ 14.65                                | psia   |                     |   | Delive                   | erability                              |  |                             |  |          | <u> </u>                          | victd @   | 14.65 ps             | ia   |   |  |
| facts stated  | therein, and  |   |         | uthority, | , on behalf                              | of the Comp  | any, sta<br>recuted |   | he is du                 | •                                      |  |                             | he above                                       | Dece     | d that t                          | e has kn  | owledge o            |  | 2013  |  |
|   |   |   | Witness | s         |  |  |                     | _   |                          |  | -  |                             |  |          |                                   | USA<br>Compar                                   |                      |  |   |  |
|   |   |   |         |           |  |  |                     |   |                          |  |  |                             |  |          |                                   |   |                      | Δ  |   |  |
|   |   |   |         |           |  |  |                     |   |                          |  |  |                             |  | 1        | 4ime                              | e Lan   | nou /                | Ju .   | nelta   |  |

DEC 27 2013

| I declare under penalty of perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator OXY USA Inc. and that the foregoing pressure information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon available production summaries and lease records of equipment installation and/or upon type of completion or upon use being made of the gas well herein named.  I hereby request a one-year exemption from open flow HERRICK 4-G27-30-40 for the gas well on the grounds that said well: |
|--|
| (Check one)  |
| is a coalbed methane producer  |
| is cycled on plunger lift due to water   |
| is a source of natural gas for injection into an oil reservoir undergoing ER   |
| is on a vacuum at the present time; KCC approval Docket No.  |
| is not capable of producing at a daily rate in excess of 250 mcf/D   |
| I further agree to supply to the best of my ability any and all supporting documents deemed by Commission staff as necessary to corroborate this claim for exemption from testing.   |
| Date:December 20, 2013   |
|  |
|  |
|  |
|  |
|  |
|  |
| Signature: OXY USA Inc   |
| Title: Gas Business Coordinator  |

Instructions: If a gas well meets one of the eligibility criteria set out in the KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31st of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.

DEC 27 2013
RECEIVED