## KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

· •

| Type Test  | t:           |   |                                     |  | 6   | See Instruct                                | ions on Reve  | rse Side  | )           |  |   |                              |   |  |
|--|--------------|---|-------------------------------------|--|---|---|---|---|-------------|--|---|------------------------------|---|--|
| ✓ Open Flow  |              |   |                                     |  | <b>=</b> . 5                                | <b>T.</b> 18.00                             |   |   |             | N= 45  |   |                              |   |  |
| Deliverabilty  |              |   |                                     |  | Test Date: 9/24/13                          |   |   | API No. 15<br>047- <b>25:04 20,05/ - 0000</b>   |             |  |   |                              |   |  |
| Company<br>BEREXCO LLC   |              |   |                                     | 0/20   | Lease<br>CARLSON                            |   |   | 1   |             |  | Well Number   |                              |   |  |
| County Location EDWARDS C NW NW                                      |              |   |                                     | Section<br>12  |   | TWP   |   |   |             | Acres Attributed   |   |                              |   |  |
| Field  |              |   |                                     |  | Reservoir CHEROKEE                          |   |   | Gas Gathering Connection<br>SEM GAS   |             |  |   |                              |   |  |
| Completion Date  |              |   |                                     |  | Plug Back Total Depth                       |   |   | Packer S  | et at       | ħ  |   | <del></del> .                |   |  |
|  |              |   |                                     | Internal E   | liameter                                    | Set at<br>4458                              |   | Perforations<br>4407  |             | To<br>4412   | то<br>4412  |                              |   |  |
| Tubing Size 2 3/8  |              |   | Weigh                               | t  | Internal D                                  | Internal Diameter<br>N/A                    |   | Set at 4460   |             | Perforations   |   | То                           |   |  |
| Type Con   |              |   |                                     | N. 1-  | Type Flui                                   | Type Fluid Production WATER                 |   |   |             | Pump Unit or Traveling Plunger? Yes / No FLOWING                       |   |                              |   |  |
| SINGLE GAS Producing Thru (Annulus / Tubing)                         |              |   |                                     | % C  | % Carbon Dioxide                            |   |   | % Nitrog  | en          |  | Gas Gravity - G                                     |                              |   |  |
| TUBING   |              |   |                                     | 0.3054   | 0.3054                                      |   |   |   | ¥1<br>      | 0.840  |   |                              |   |  |
| Vertical Depth(H) 4460   |              |   |                                     |  |   | Pressure Taps<br>FLANGE                     |   |   |             |  | 4.028   |                              | over) Size                                    |  |
| Pressure   | Buildup      | n: 4  | Shut in                             | 3/ 2   | 13 at 10                                    | MA 00:0                                     | (AM) (PM) T   | aken_9/:  | 24/         | 20   | 13 at 10:00 /                                       | <u>AM</u> _ (/               | AM) (PM)                                      |  |
| Well on L  | .ine:        |   | Started                             | 2  | 0 at  |   | (AM) (PM) 1   | aken  |             | 20   | at  | (/                           | AM) (PM)                                      |  |
|  | <del></del>  |   | Circle one:                         |  | Γ   | OBSERVE                                     | D SURFACE   |   | ı -         |  | Duration of Shut-                                   | in_24                        | Hours   |  |
| Static /<br>Dynamic<br>Property                                      | Dynamic Size |   | Meter<br>Prover Pressu<br>psig (Pm) | Pressure Differential in Inches H <sub>2</sub> 0   | Flowing<br>Temperature<br>t                 | Temperature Temperature                     |   | Casing Wellhead Pressure (P <sub>w</sub> ) or (P <sub>t</sub> ) or (P <sub>c</sub> )  psig psia |             | ubing<br>ad Pressure<br>(P <sub>1</sub> ) or (P <sub>c</sub> )<br>psia | Duration<br>(Hours)                                 | Liquid Produced<br>(Barrels) |   |  |
| Shut-In  |              |   |                                     |  |   |   | 600   | рэн   | psig<br>550 | psia   | 24  |                              |   |  |
| Flow   |              |   |                                     |  |   |   |   |   |             |  |   |                              |   |  |
|  |              |   |                                     |  |   | FLOW STR                                    | EAM ATTRIE  | UTES  |             |  |   |                              |   |  |
| Plate<br>Coeffiecient<br>(F <sub>b</sub> ) (F <sub>p</sub> )<br>Mcfd |              | Circle one:<br>Meter or<br>Prover Pressure<br>psia              |                                     | Press<br>Extension<br>✓ P <sub>m</sub> x h   | Grav<br>Fact                                | tor   | Flowing<br>Femperature<br>Factor<br>F <sub>11</sub> | mperature Factor  |             | Metered Flov<br>R<br>(Mcfd)  | GOR<br>(Cubic Fe<br>Barrel)                         |                              | Flowing<br>Fluid<br>Gravity<br>G <sub>m</sub> |  |
|  |              |   | <u> </u>                            |  |   | ·   |   | <u> </u>  |             |  |   |                              |   |  |
| (P <sub>c</sub> ) <sup>2</sup> =                                     |              |   | (P <sub>w</sub> )² =                | :  | (OPEN FLO                                   |   | ERABILITY)  | CALCUL<br>- 14.4) +   |             | :  | (P <sub>a</sub> ) <sup>;</sup><br>(P <sub>d</sub> ) | <sup>2</sup> = 0.20          | )7  |  |
| $(P_c)^2 - (P_A)^2$ or $(P_c)^2 - (P_d)^2$                           |              | (P <sub>c</sub> ) <sup>2</sup> - (P <sub>w</sub> ) <sup>2</sup> |                                     | Choose formula 7 or 2  1. P <sub>c</sub> <sup>2</sup> - P <sub>d</sub> <sup>2</sup> 2. P <sub>c</sub> <sup>2</sup> - P <sub>d</sub> <sup>2</sup> divided by: P <sub>c</sub> <sup>2</sup> - P | LOG of<br>formula<br>1. or 2.<br>and divide | LOG of formula 1. or 2. and divide p 2. p 2 |   | Backpressure Curve Slope = "n" or Assigned Standard Slope                                       |             | .og  | Antilog   | Op-<br>Deli<br>Equals        | en Flow<br>verability<br>R x Antilog<br>Mcfd) |  |
|  |              |   |                                     | - 6 '9   |   |   |   |   |             |  |   |                              |   |  |
|  |              |   |                                     |  |   | <del></del>                                 |   |   |             |  | <del></del>   |                              |   |  |
| Open Flo   | w            |   |                                     | Mcfd @ 14  | .65 psia                                    |   | Deliverabili  | ty  |             |  | Mcfd @ 14.65 psi                                    | ia                           | <del></del>                                   |  |
|  |              | _   | -                                   |  |   |   |   |   |             |  | rt and that he ha                                   |                              |   |  |
| the facts s  | stated th    | erei  | n, and that sa                      | aid report is tru  |   | RI  | this the 231<br>ECEIVED<br>PRATION COMI             | /   | day of      | ecember  |   | , 2                          | 20  |  |
|  |              |   | Witness (                           | f any)   |   |   |   |   | OWN         | For  | Company   |                              |   |  |
|  |              |   | For Comm                            | ission   |   | DEC   | 2 6 20 <del>13</del>                                |   |             | Chec   | ked by  |                              |   |  |

CONSERVATION DIVISION WICHITA KS

| exempt status und<br>and that the forest<br>correct to the best<br>of equipment insta<br>I hereby requi | der Penalty of perjury under the laws of the state of Kansas that I am authorized to request der Rule K.A.R. 82-3-304 on behalf of the operator BEREXCO LLC going pressure information and statements contained on this application form are true and t of my knowledge and belief based upon available production summaries and lease records allation and/or upon type of completion or upon use being made of the gas well herein named. est a one-year exemption from open flow testing for the CARLSON #1 counds that said well: |
|---|---|
| (Check  | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No is not capable of producing at a daily rate in excess of 250 mcf/D   |
| _   | e to supply to the best of my ability any and all supporting documents deemed by Commission y to corroborate this claim for exemption from testing.   |
|   | RECEIVED NSAS CORPORATION COMMISSION  DEC 2 6 2013  CONSERVATION DIVISION WICHITA, KS  PETROLEUM ENGINEER   |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.