

1 080477

15-007-19092-0000

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION C SW SE  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- Completed 1-9-59  
SEC. 29 T. 33 S. R 14 W/EX

660 feet from S section line

1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5144

Lease Name Zundle Well # 1

Operator: Mull Drilling Company, Inc.

County Barber 153.24

Name: P. O. Box 2758

Well Total Depth 4715 feet

Address: Wichita, KS 67201

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 769

Abandoned Oil Well \_\_\_\_\_ Gas Well X Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Mull Drilling Company, Inc. License Number 5144

Address P. O. Box 2758, Wichita, KS 67201

Company to plug at: Hour: 11:00 am Day: 24 Month: January Year: 19 86

Plugging proposal received from Gene Brown

(company name) Mull (phone) 316-264-6366

were: 5 1/2" at 4715' Perfs at 4652-4672' Casing collapsed -- unable to reenter

1st plug pump 140 sx cement down 5 1/2"

2nd plug pump 160 sx cement down 8 5/8"

Plugging Proposal Received by Richard W. Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 2:00 pm Day: 24 Month: January Year: 19 86

ACTUAL PLUGGING REPORT Pumped 2 sx hulls, 50 sx cement 2% cc, 10 sx gel, 150 sx cement,  
released 8 5/8" rubber plug and pumped 125 sx cement. Shut in pressure 300 psi

Pumped 4 sx hulls, 5 sx gel, and 125 sx cement down 8 5/8".

RECEIVED  
STATE CORPORATION COMMISSION  
JAN 30 1986  
1-30-86  
CONSERVATION DIVISION

Maximum pressure 100 psi and shut in 50 psi

Remarks: No Recovery. Cemented by Halliburton.

(If additional description is necessary, use BACK of this form.)

INVOICED (If possible) observe this plugging.

Signed J. L. Metz / rjl  
(TECHNICIAN)

DATE JAN 31 1986

INV. NO. 12217