To:		API NUMBER 15-	033-20,668	-00.00
STATE CORP	ORATION COMMISSION ON DIVISION - PLUGGING SECTION C			
200 COLORADO DERBY BUILDING				
WICHITA, K	ANSAS 67202			m S section 1 i
TECHNICIAN	I'S PLUGGING REPORT	4620	feet fro	n E section ii
Operator L	icense / 9657	Lease Name <u>Mo</u>	Laughlin	Hell #1-22
Operator:	Quintana Petroleum Corporation	County	Comanche	168.84
Name& Address	818 17th St., Suite 610	Well Total Dep	th5	195 fe
	Denver, CO 80202	Conductor Pipe	: Size	feet
		Surface Casing	: \$1ze 8 5/	feet
	Oli WellGas Well			
				Dan X
	as hereinafter indicated			
Plugging C	Contractor Aldebaran Drilling Co.,	Inc.	License N	umber 5829
Address	Box 18611, Wichita, KS 67207		 	., ,
Company to	o plug at: Hour:_noon Day:7	Month:	January	Year: 19 85
			<u> </u>	
	proposal received from To			
(company n	ame) Aldebaran	····	(ph	one) 316-685-5372
were:	to fill hole with heavy mud and	spot cement throu	ıgh drill pi	pe
lst plug a	t 1080' with 50 sx cement		27	RECEIVEL
6.8		- <u> </u>	S <u>U</u>	ALE PROPORATION COMM
	t 500' with 50 sx cement olid bridge			JAN 2 3 1985
	ulls - plug at 40' cement to s	urface with 10 sx	cement	
5th plug t	o circulate rat hole with 15 sx co	ement		CONSERVATION DIVISION Wichita, Kansas
6th plug t	o circulate mouse hole with 10 sx	cement sai Received by	T 71 M-4-	
	Flugging Flops	sal kecelved by	J. H. Metz (TE	CHNICIAN)
Pluasina (Operations attended by Agent?: Al	t Part		None X
	s Completed: Hour: 1:15 pm Day: 7			
				
	ugging REPORT 1st plug at 1080' w	-		
sx cement,	3rd & 4th plugs - solid bridge -	hulls - plug at	40' ceme	nt to surface
	cement, 5th plug to circulate rate	t hole with 15 sx	cement, 6t	h plug to
with 10 sx	cement, but plug to circulate la			
	······································			
	mouse hole with 10 sx cement.			
	······································			
	······································			
circulate	mouse hole with 10 sx cement.			
circulate	mouse hole with 10 sx cement.	Sun		
circulate Remarks: U	mouse hole with 10 sx cement. Sed 60/40 Pozmix 2% gel 3% cc b6 s	Sun		
circulate	mouse hole with 10 sx cement. Sed 60/40 Pozmix 2% gel 3% cc b6 statement.	Sun		

FORM CP-2/3 Rev.01-84