

1060273

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 165-21,232 -00-0

SW NW SE, SEC. 13, T 17 S, R 18

1650 feet from N/S section line

2310 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5140

Lease Name Weigand Well # 2

Operator: Frontier Oil Company

County Rush

Name & Address: 1720 Kansas State Bank Building  
Wichita, KS 67202

Well Total Depth 3682 119.67 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 595

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 3:00 pm Day: 19 Month: July Year: 19 84

Plugging proposal received from Walter Oden

(company name) Red Tiger (phone) 316-263-2371

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 1180' with 50 sx cement

2nd plug at 640' with 50 sx cement  
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement

5th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Paul A. Luthis (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 4:45 pm Day: 19 Month: July Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 1180' with 50 sx cement, 2nd plug at 640' with 50 sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 5th plug to circulate rat hole with 15 sx cement.

RECEIVED STATE CORPORATION COMMISSION

JUL 24 1984

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Allied.  
(if additional description is necessary, use BACK of this form.)

CONSERVATION DIVISION  
Wichita, Kansas

INVOICED

DATE 7-30-84

INV. NO. 2723

7-19

Signed Paul A. Luthis (TECHNICIAN)