

1 060031

8-26

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-033-20,790 - 00-00
90' S & 180' E OF
C N/2 NW, SEC. 17, T 31 S, R 17 W/E
4530 feet from S section line
3780 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5178
Operator: Sidwell Oil & Gas, Inc.
Name & Address P.O. Box 2475
Pampa, TX 79065

RECEIVED
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
WICHITA, KANSAS
AUG 29 1990

Lease Name Huff Well # 3-17
County Comanche 169.00
Well Total Depth 5200 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 620

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Trans-Pac Drilling Inc. License Number 5841

Address One Main Place, #410, Wichita, KS 67202

Company to plug at: Hour: 1:30 a.m. Day: 26 Month: 8 Year: 1990

Plugging proposal received from Gary Pugh

(company name) Trans-Pac Drilling Inc. (phone) 316-265-0226
Elevation 2132'

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1050'

1st plug at 1100' with 50 sx cement,

2nd plug at 650' with 50 sx cement,

3rd plug at 40' with 10 sx cement, 4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Case Morris (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 3 a.m. Day: 26 Month: 8 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug at 1100' with 50 sx cement,

2nd plug at 650' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement,

Water well plugged with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(If additional description is necessary, use BACK of this form.)

INVOICED

(If not) observe this plugging.

DATE: 8-30-90

Signed Case Morris (TECHNICIAN)

INV. NO. 29184
8-26