

STATE OF KANSAS
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
200 Colorado Derby Building
Wichita, Kansas 67202

FORM CP-1
Rev. 2/89

WELL PLUGGING APPLICATION FORM
(File One Copy)

API NUMBER 15-077-20899-00-00 (of this well).
(This must be listed; if no API# was issued, please note drilling completion date.)

WELL OWNER/OPERATOR McCoy Petroleum Corporation OPERATOR'S LICENSE NO. 5003

ADDRESS 110 South Main Suite 500 Wichita, Ks 67202 PHONE # (316) 265-9697

LEASE (FARM) Slagell "A" WELL NO. #1 WELL LOCATION C-SE-NE COUNTY Harper

SEC. 26 TWP. 32 RGE. 8W (E) or (W) TOTAL DEPTH 3952' PLUG BACK TD 3911'

Check One:

OIL WELL GAS WELL D & A SWD or INJ WELL DOCKET NO. _____

SURFACE CASING SIZE 8-5/8" SET AT 262' CEMENTED WITH 200 SACKS

CASING SIZE 4-1/2" SET AT 3947' CEMENTED WITH 200 SACKS

PERFORATED AT 3646'-3660' 4/spf

CONDITION OF WELL: GOOD POOR CASING LEAK JUNK IN HOLE

PROPOSED METHOD OF PLUGGING Set CIBP @ +-3600' (keep within 100' of base of 4 1/2".) Cap

with 2 sacks of cement. Shoot 4 1/2" according to stretch on pipe. Pull 4 1/2" to 1270' spot

25 sacks of cement. Pull 4 1/2" to 820' spot 25 sacks cement. See back side

(If additional space is needed use back of form.)

IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? IS ACO-1 FILED?
(If not explain.)

DATE AND HOUR PLUGGING IS DESIRED TO BEGIN Will Notify KCC

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-101 et. seq. AND THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

NAME OF REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:

Daryl Hanson PHONE # (316) 532-5292

ADDRESS Kingman, Kansas

PLUGGING CONTRACTOR Hayes Well Service LICENSE NO. 5429

ADDRESS Attica, Kansas PHONE # (316) 254-7204

PAYMENT OF THE PLUGGING FEE (K.A.R. 82-3-118) WILL BE GUARANTEED BY OPERATOR OR AGENT.

SIGNED: [Signature]
(Operator or Agent)

DATE: 6-3-90

JUN 11 1990
6-11-90
CONSERVATION DIVISION
Wichita, Kansas

2

Pull 4½" to 316' circulate cement to surface. Pull remaining 4½" casing from hole. Top off 8-5/8" with cement. Cut off 8-5/8" 3' below ground level.