

1 010161

15-007-30279-0001

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- Completion date 11/23/66  
C SE SE, SEC. 16, T 30 S, R 12 (W/8)  
660 feet from S section line  
660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5087

Lease Name Lawrenz Well # 4

Operator: Texas Energies, Inc.  
Name & Address: P.O. Box 947  
Pratt, KS 67124

County Barber 94.90  
Well Total Depth 2920 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 275

Abandoned Oil Well  Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Wheatstate Oilfield Services License Number 5149

Address P.O. Box 329 Pratt, KS 67124

Company to plug at: Hour: 12 p.m. Day: 19 Month: 8 Year: 1986

Plugging proposal received from Ted Moff

(company name) Wheatstate Oilfield Services (phone) 316-672-7514

were: 5 1/2" at 2900' Perfs 2734-2740 Elevation 1779' GL

1st plug Pump to bottom with 25 sx of common cement followed by 20 bbls of mud.

2nd plug squeezed well with 2 sx hulls, and 80 sx of Halco lite cement.

Plugging Proposal Received by Jack Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 12:20 p.m. Day: 19 Month: 8 Year: 1986

ACTUAL PLUGGING REPORT 1st plug pump to bottom with 25 sx of common cement followed by 20 bbls of mud.

2nd plug squeezed well with 2 sx hulls and 80 sx of Halco lite cement.

Maximum pressure 400 psi and shut in 275 psi

Remarks: Recovered 1040' of 5 1/2" casing. Halliburton pumped Halco Lite.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
AUG 22 1986  
observe this plugging.

Signed *Jack Luthi* (TECHNICIAN)

DATE \_\_\_\_\_  
INV. NO. 14810