Kansas Corporation Commission One Point Stabilized Open Flow or Deliverability Test

Type Test	:						(See Instruc	tions on Reve	erse Side))					
Ор	en Flo	W				T4 D-4-				4011	J. 45				
√ De	liverat	ilty				Test Date 01/27/2	: 2014 - 01/	/28/2014			No. 15 047-20,299	- 9001			
Company F.G. Ho		mp	any, L.L.C					Lease MUNDH	IENKE			1-30	Well No	ımber	
County Location Edwards 3440FSL,3740FE			Section 30		TWP 26S			E/W)		Acres Attributed					
Field			01101	<u> </u>	77 101 2	Reservoir	•				ering Connec	tion			
Munder						Mississippi				Prairie Pipeline					
Completic 11/21/7			2/92			Plug Back Total Depth				Packer S	et at				
Casing Si		3110	Weigh	nt		Internal Diameter Set at			Perfor	То	То				
4-1/2" 10.5#					4605'		4471'-4477'								
Tubing Size 2-3/8"	Tubing Size Weight 2-3/8" 4.7#			Internal Diameter Set at 4410')¹	Perfor	ations	То	То				
Type Completion (Describe) Single (Gas)				Type Fluid	Type Fluid Production				Pump Unit or Traveling Plunger? Yes / No Pump Unit						
			ulus / Tubing)		% Carbon Dioxide				% Nitrogen Gas Gravity - G					
Tubing															
Vertical D	epth(F	1)					Pressu Flan	ire Taps ge				(Meter F 2''	Run) (Pr	over) Size	
Pressure	Buildu	p: :	Shut in01	/27/2	2014 19	at _8	:00	(AM) (PM) 1	Taken 0	1/27/201	4 19	at 8:00		(AM) (PM)	
Well on Li	ine:									1/28/201	19	at <u>9:00</u>		(AM) (PM)	
							OBSERVE	D SURFACE	DATA			Duration of Shut	-in	Hours	
Static / Orifice Dynamic Size Property inches		e.	Circle one: Meter or Prover Pressure		Pressure Differential in (h)	Flowing Well Hear Temperature Temperatu		Mellhead Pressure		Tubing Wellhead Pressure (P _w) or (P _t) or (P _c)		Duration (Hours)	1 '	Liquid Produced (Barrels)	
Property Shut-In	incr	es	psig	ln	iches H ₂ 0	t	t	psig 443	psia	psig	psia	24			
Flow	•							88		90		24			
			<u> </u>	l	1		FLOW STR	EAM ATTRIE	BUTES		<u> </u>		<u>l</u>	•	
Plate Coefficient (F _b) (F _p) Mcfd		Pro	Circle one: Meter or Prover Pressure psia		Press Grav Extension Fact Š P _m x H _w F _g		tor Temperature		Deviation Factor F _{pv}		Metered Flow R (Mcfd)	GOR (Cubic Fe Barrel)	eet/	Flowing Fluid Gravity G _m	
$(P_c)^2 = 45$	5.967	, .	(P _w) ² =	. 25.0	090 .	(OPEN FLO	, ,	ERABILITY)	CALCUL. - 14.4) +			(P _a))2 = 0.2	07	
(' c'					formula 1 or 2:	' a		T	sure Curve	14.4 -		(F _d ,	T		
(P _c) ² - (For or (P _c) ² - (For example)	- I	(F	P _c) ² - (P _w) ²	2.	$P_{c}^{2} - P_{a}^{2}$ $P_{c}^{2} - P_{d}^{2}$ by: $P_{c}^{2} - P_{w}^{2}$	LOG of formula 1. or 2. and divide by:	P _c ² - P _w ²	Slope	= "n" or gned	nxL	og	Antilog	Dei	pen Flow liverability s R x Antilog Mcfd	
One= 51:	l				ше	i-		Dall and Maria					<u></u>		
Open Flow					fd @ 14.6		· · · · · · · · · · · · · · · · · · ·	Deliverability				cfd @ 14.65 psi			
			authority, on at said report					000			ve report and	that he has knov	vledge o	f the facts	
					F-1- F-1-1			CC WI	-	Ĭ	vene	285	h)	gaze	
			Witness (FEB 03				ompany	U		
			For Comr	เมรรเดก			'				Check	ea by			

exempt status under Rule and that the foregoing information the best of my knowledge tion and/or of type complete.	Ity or perjury under the laws of the state of Kansas that I am authorized to request K.A.R. 82-3-304 on behalf of the operatorF.G. Holl Company, L.L.C. ormation and statements contained on this application form are true and correct to e and belief based upon gas production records and records of equipment installation or upon use of the gas well herein named. manent exemption from open flow testing for theMUNDHENKE 1-30 hat said well:
is cycle is a so is on v	albed methane producer ed on plunger lift due to water urce of natural gas for injection into an oil reservoir undergoing ER acuum at the present time; KCC approval Docket No pable of producing at a daily rate in excess of 250 mcf/D
Date: 01/31/2014	
	Signature:

Instructions:

All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.

FEB 03 2014