

To: 1 040701
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-007-22,383 0000 22
C NE SE, SEC. 3, T 30 S, R 13 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 5056
Operator: F.G. Holl Company
Name & Address 6427 E. Kellogg
P.O. Box 780167
Wichita, KS 67278-0167

1980 feet from S section line
660 feet from E section line
Lease Name Eckles Well # 1-3
County Barber 151.94
Well Total Depth 4675 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 13 3/8 feet 232

Abandoned Oil Well Gas Well _____ Input Well _____ SWD Well _____ D&A _____
Other well as hereinafter indicated _____

Plugging Contractor Pratt Well Service License Number 5893
Address P.O. Box 847, Pratt, KS 67124

Company to plug at: Hour: 10:30 a.m. Day: 7 Month: 10 Year: 19 92

Plugging proposal received from Bruce Wagner
(company name) Pratt Well Service (phone) 316-672-2531

were: 4 1/2" at 4669' w/225 sx cement, PBD 4621', Perfs at 4254-62'
1st plug sand back to 4200' and dump 4 sx cement on top of sand through bailer,
2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release wiper plug
and pump 225 sx cement.

Plugging Proposal Received by Steve Middleton
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 11:15 a.m. Day: 7 Month: 10 Year: 19 92

ACTUAL PLUGGING REPORT 1st plug sanded back to 4100' and dumped 4 sx cement on top of sand
bridge through bailer,

2nd plug pumped down 13 3/8" surface pipe with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel
100 lbs. hulls, and 225 sx cement.

Maximum pressure 400 psi and shut in 150 psi.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. Recovered 2574' of 4 1/2" casing.
(if additional description is necessary, use BACK of this form.)

I (did not) observe this plugging.

DATE 10-29-92
WV. NO. 36635

Signed Stephen J. Ober
(TECHNICIAN)

RECEIVED
STATE CORPORATION COMMISSION
OCT 9 1992
10-9-92
CONSERVATION DIVISION
Wichita, Kansas