

1 060044

11-1

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-033-20,793-00-00  
200' E of  
C SE SW, SEC. 30, T 32 S, R 16 W/R

TECHNICIAN'S PLUGGING REPORT

660 feet from S section line

3100 feet from E section line

Operator License # 4581

Lease Name Standish Well # 1

Operator: EXOK, Inc.

County Comanche 176.31

Name & Address 6410B North Santa Fe

Well Total Depth 5425 feet

Oklahoma City, OK 73116

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 463

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 KSB & T Bldg., Wichita, KS 67202

Company to plug at: Hour: 6:30 a.m. Day: 1 Month: 11 Year: 19 90

Plugging proposal received from Mike Rempe

(company name) Red Tiger Drilling Company (phone) 316-263-2371

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1911'

1st plug at 920' with 50 sx cement, 2nd plug at 485' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Case Morris  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 8:30 a.m. Day: 1 Month: 11 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug at 920' with 50 sx cement,

2nd plug at 485' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED  
NOV 5 1990

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED

(operator) observe this plugging.

DATE 11-19-90

Signed Case Morris  
(TECHNICIAN)

INV. NO. 30012

11-1