4,7.	<b>L</b>		L	ANICACO		CON CORR	MICCION					
		ONE				TION COM		ITV TECT	r			
Type Test					STABILIZED OPEN FLOW OR DELIVERABILITY TEST (See Instructions of Reverse Side)						G-2	
X	Open Flo	w		(Occ mo	pacpons of they	erse didey				(Rev:	6/98)	
F	Deliverab	ility		Test Date:	: 3/5/14		API No. 15-	129 20351	-0000			
Company	<u> </u>			<del></del>	Lease					Well Numbe	ı	
ANADARKO E&P ONSHORE				DUNKLE			C-1_			C-1		
County	•		Section						RNGE (E/W)	•		
MORTON Field		1980 FNL 8	Reservoir	•	24		33 Gas Gathering G	`annostion	<u>41</u>		0	
PANOMA UI	NALLOCA	TED	COUNCI	. GROVE			Gas Gallering C		RKO GATH	ERING		
Completion Date			Plug Back To	_		,		Packer Set a				
03/16/78				<u> 2</u> 606	•				n/a			
Casing Size			Weight		Interenal Diam		Set at		Perforations	Т	_	
4.5 ubing Size		10.5 4.052 Weight Interenal Diamete			2800 Set at		2484 Perforations	т	2575			
2.375			4.7		1.995		2598		NA	NA	U	
Type Completion (	(Describe)		Type Fluid Pr	oduction	Reservoir Terr		Pump Unit or Tra	aveling Plunge		Yes / No		
SINGLE GAS			WATER 130			)	Pumping Unit			<u>P</u> mp		
Producing Thru (Annulus / Casing)			% Carbon Dioxide				% Nitrogen		Gas Gravity -	· G <sub>g</sub>		
Casing		<del></del>		0.135			16.848		0.733			
Vertical Depth (H) 2529				Pressure Tap	S		(Meter Run) X		(PROVER)	Siz	e 1	
Pressure Buildup:		Shut in	3/4/14		11:15 am	(AM)(PM)		3/5/14	at	11:15 am	(AM)(PM)	
Well on Line:		Started		-	N/A	(AM)(PM)	Taken			N/A	(AM)(PM)	
	-			ORSE	RVED SURI	FACE DATA		Duration of Sh	ut-in	24	4 Hours	
	Circle One:		OBSERVED SURFACE DAT				Casing Tubing			<u>-</u> _	Liquid	
Static /	Orifice	Meter or	Differential	Flowing	Well Head	1	ad Pressure	Wellhead Pressure		Duration	Produced	
Dynamic	Size	Prover Pressure	in (h)	Temperature	Temperature		(P <sub>1</sub> ) or (P <sub>n</sub> )	-	P <sub>i</sub> ) or (P <sub>c</sub> )	(Hours)	(Barrels)	
Property	inches	psig	Inches H <sub>2</sub> O	t t	t	psig 9	psia	psig	psia	24	-	
Shut-In Flow	0.625	N/A	N/A	N/A	60	N/A	23.4 0	Pmp Pmp		24 N/A	N/A	
1 1017	0.020	1071	1477	1 1477	00	1477		1 1 1 1 P		14// 1	1 1477	
			<del>-</del>	FLO	N STREAM	ATTRIBUTES	S	<del></del>				
Plate Coefficient	1	Circle One:		0	Flowing	Davistica	Madage d Flagge		005		Flowing	
$(F_b)(F_p)$	Meter or Prover Pressure		Extension Sqrt	Gravity Factor	Temperature Factor	Deviation Factor	Metered Flow R	GOR (Cubic Feet/		1	luid	
Mcfd	psia		((Pm)(Hw))	F <sub>a</sub>	Factor F <sub>ft</sub>	F <sub>DV</sub>	(Mcfd)	(Cubic reev Barrel)		Gravity G <sub>m</sub>		
1.927		14.4		1.168	1.063	1.000	0	0		0.000		
	l		(00	•	DEL BIEDAE	·	NIII ATIONO	<del> </del>				
			(UP	EN FLOW) (	DELIVERAE	BILITY) CALC	CULATIONS			(P <sub>w</sub> ) <sup>2</sup> =0.207		
(P <sub>c</sub> ) <sup>2</sup> =	0.548	(P <sub>w</sub> ) <sup>2</sup> =	0	P₀=		%	(P <sub>c</sub> -14.4)+14.4=			$(P_d)^2 = $		
		Choose formula 1 or 2;	LOG of		Backpressure Curve Slope = "n"		n x LOG()		Antilog	Open Flow Deliverability Equals R x Antilog		
$(P_c)^2 - (P_a)^2$		1. P <sub>c</sub> <sup>2</sup> -P <sub>a</sub> <sup>2</sup>	formula									
or (P <sub>c</sub> ) <sup>2</sup> -(P <sub>d</sub> ) <sup>2</sup>	$(P_c)^2 - (P_w)^2$	2. P <sub>c</sub> <sup>2</sup> -P <sub>d</sub> <sup>2</sup>	1. or 2.	$(P_{c}^{2}-P_{w}^{2})$								
		divided by	and divide		Assigned					Mcfd		
0.044	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>		by:		Standard Slope		0.494		0.050			
0.341 0.548 0.622		-0.206		0.878		-0.181		0.659	-	0		
<u>-</u>							1		<u> </u>	<u> </u>		
Open Flow					Deliverabili	ty						
The undersia	ned authorit	v on behalf of t	he Compan	v states that	ha is duly a	ithorized to m	nake the above	renort and t	hat he hae l	cnowledge		
							lay of March 2		at no nao r	omouge		

Witness (if any)

For Commission

KCC WICHITA

Checked by

For Company

Thomas L. Walsh

APR 0 2 2014

RECEIVED

العشران 🛈

Instructions All active gas wells must have at least on original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calender year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall therafter be reported yearley in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.

APR 0 2 2014 RECEIVED