

020191

11-24

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 007-22,209-00-01
E/2 NE SE, SEC. 10, T 30 S, R 13 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 3536

1980 feet from S section line

535 feet from E section line

Operator: Ramco Oil & Gas Corporation

Lease Name Eugene R. Lawrenz Well # 1 (OWWO)

Name & Address P.O. Box 99

County Barber 154.86

Well Total Depth 4765 feet

Belpre, OH 45714

Conductor Pipe: Size feet

Surface Casing: Size 10 3/4 feet 258

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 3 a.m. Day: 24 Month: 11 Year: 19 88

Plugging proposal received from Harold Maley

(company name) Abercrombie Drilling, Inc. (phone) 316-262-1841

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 790' with 50 sx cement,

2nd plug at 270' with 40 sx cement,

3rd plug at 40' with 15 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Glenn R. Barlow (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour 5:30 a.m. Day: 24 Month: 11 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 790' with 50 sx cement,

2nd plug at 270' with 40 sx cement,

3rd plug at 40' with 15 sx cement,

4th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.

(if additional description is necessary, use BACK of this form.)

INVOICED (if not observed this plugging.)

DATE DEC 1 1988

Signed Glenn R. Barlow (TECHNICIAN)

INV. NO. 23214 11-24

RECEIVED
STATE CORPORATION COMMISSION
NOV 20 1988
11-27-88
CONSERVATION DIVISION
Wichita, Kansas

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... 11 21 88 month day year

API Number 15-007-22,209-A-0001

OPERATOR: License # 3536 Approx Name Ramco Oil & Gas Corporation Address P. O. Box 99 City/State/Zip Belpre, OH 45714 Contact Person Jack L. Partridge Phone (316) 262-1841

E/2 NE SE Sec. 10 Twp. 30 S, Rg. 13 East X West 1980 Ft. from South Line of Section 535 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 535 feet County Barber

CONTRACTOR: License # 5422 Name Abercrombie Drilling, Inc. City/State Wichita, KS 67202

Lease Name Eugene R. Lawrenz Well # 1 (OWWO) Ground surface elevation 1855 feet MSL

Well Drilled For: X Oil Storage Infield X Mud Rotary Gas Inj Pool Ext Air Rotary X OWWO Expl Wildcat Cable

Domestic well within 330 feet yes X no Municipal well within one mile yes X no

If OWWO: old well info as follows: Operator Ramco Oil & Gas Corporation Well Name Eugene R. Lawrenz #1 Comp Date 10-31-88 Old Total Depth 4765'

Depth to bottom of fresh water 150' Depth to bottom of usable water 200'

Surface pipe by Alternate 1 X 2 Surface pipe planned to be set at 258'

Conductor pipe required N/A Projected Total Depth 4765 feet

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 11-18-88 Signature of Operator or Agent Jack L. Partridge Title Vice President

Formation Arbuckle

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 258' feet per Alt. 1 X This Authorization Expires 5-18-89 Approved By LRM 11-18-88

EFFECTIVE DATE: 11-23-88

11-22-88

NO wt well

Approx E/2 NE SE Sec. 10 Twp. 30 S, Rg. 13 East X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. Top of Arbuckle or formation with 25 SX feet of 60/40 posmix, 3% gel... 2nd plug @ ft. deep. Top of Anhydrite or formation with 50 SX feet of 60/40 posmix, 3% gel... 3rd plug @ ft. deep 250' or formation with 50 SX feet of 60/40 posmix, 3% gel... 4th plug @ ft. deep 40' or formation with 10 SX feet of 60/40 posmix, 3% gel... 5th plug @ ft. deep or formation with feet of... (2) Rathole to surface minus 5 feet 10 sx of 60/40 posmix, 6% gel (b) Mousehole to surface minus 5 feet

PUSHER HAROLD M. LAY TD 4765 FORMATION SURFACE PIPE 10 3/4 @ 258 ANHYDRITE ELEVATION 11-24-88 STARTING TIME & DATE 3:00 AM COMPLETION TIME & DATE 11-24-88 5:30 1st PLUG @ 790 FT. W/ 50 SX 2nd PLUG @ 270 FT. W/ 140 SX 3rd PLUG @ 40 FT. W/ 15 SX 4th PLUG @ FT. W/ SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ SX CEMENT COMPANY Halliburton TECHNICIAN S.P.

60/40 RECEIVED STATE CORPORATION COMMISSION NOV 29 1988 11-27-88 CONSERVATION DIVISION Wichita, Kansas