

5-16-88

1051048

API NUMBER 15- 033-20,724-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

E/2 NE NE, SEC. 24, T 33 S, R 16 W/E

4620 feet from S section line

330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5565

Lease Name Merrill Well # 1

Operator: National Cooperative Refinery Assoc. County Comanche 175.99

Name & Address Box 6

Well Total Depth 5415 feet

Great Bend, KS 67530

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 500

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 4 a.m. Day: 16 Month: 5 Year: 19 88

Plugging proposal received from Harvey Moore

(company name) Abercrombie Drilling, Inc. (phone) 913-995-4955

work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 700'

1st plug at 5300' with 40 sx cement, 2nd plug at 700' with 40 sx cement,

3rd plug at 530' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 8 a.m. Day: 16 Month: 5 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 5300' with 40 sx cement,

2nd plug at 700' with 40 sx cement,

3rd plug at 530' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.
(If additional description is necessary, use BACK of this form.)

INVOICED
did not observe this plugging.

DATE 5-20-88

Signed Richard M. Lacey (TECHNICIAN)

INV. NO. 20997

RECEIVED
STATE CORPORATION COMMISSION

MAY 19 1988
5-19-88
CONSERVATION DIVISION
Wichita, Kansas