

To: 061159  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

11-2  
API NUMBER 15- 033-20,734-0000  
C NE NW, SEC. 12, T 33 S, R 19 W/EX  
4620 feet from S section line  
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5428

Lease Name Kaniss Well # 1

Operator: Graves Drilling Company, Inc.  
Name & Address 151 North Main, Suite 850  
Wichita, KS 67202

County Comanche 35.00

Well Total Depth 358 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size none feet

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Pickrell Drilling Company License Number 5123

Address 110 North Market, Suite 205, Wichita, KS 67202

Company to plug at: Hour: 1:30 p.m. Day: 2 Month: 11 Year: 19 88

Plugging proposal received from Danny Biggs

(company name) Pickrell Drilling Company (phone) 316-262-8427

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at bottom with 50 sx cement,

2nd plug at 200-0'.

Plugging Proposal Received by Steve Durrant  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 3 p.m. Day: 2 Month: 11 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 350' with 50 sx cement,

2nd plug at 210' with 170 sx cement, cement circulated.

12 1/4" bit and sub left on bottom.

RECEIVED  
STATE CORPORATION COMMISSION  
NOV 4 1988  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 2% gel and 3% cc by Allied.

(If additional description is necessary, use BACK of this form.)

**INVOICED**

~~Will~~ observe this plugging.

DATE 11-4-88

Signed Paul A. Luthi  
(TECHNICIAN)

INV. NO. 22899  
11-2

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... October 25, 1988

API Number 15- 033-20,734-0000

OPERATOR: License # 5428
Name Graves Drilling Co., Inc.
Address 151 N. Main, Suite 850
City/State/Zip Wichita, KS 67202
Contact Person Karen L. Seiler
Phone 316-265-7233

C NE NW Sec. 12 Twp. 33 S, Rg. 19
4620 Ft. from South Line of Section
3300 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5123
Name Pickrell Drilling Company
City/State Wichita, KS 67202

Nearest lease or unit boundary line 660 feet
County Comanche
Lease Name Kaniss Well # 1
Ground surface elevation 2068 GL feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 330'
Depth to bottom of usable water 500-400'
Surface pipe by Alternate: 1 X 2
Surface pipe planned to be set 675'
Conductor pipe required
Projected Total Depth 6100 feet
Formation Simpson

Well Drilled For: Well Class: Type Equipment:
X Oil Storage Infield Mud Rotary
X Gas Inj Pool Ext Air Rotary
OWWO Expl Wildcat Cable

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 10-17-88 Signature of Operator or Agent [Signature] Title Geologist

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 120' feet per Alt.
This Authorization Expires 1-18-89 Approved By [Signature] 10-18-88

EFFECTIVE DATE: 10-23-88

Spud 11-1-88 6 5/8" - 675'

NO WELLS

C NE NW Sec. 12 Twp. 33 S, Rg. 19 East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Cement with 60/40 Posmix, 6% Gel

1st plug @ ft. deep 50 sx. @ base of or formation with Anhydrite feet of.
2nd plug @ ft. deep 50 sx. @ base of or formation with surface feet of.
3rd plug @ ft. deep 10 sx. @ 40-0' or formation with feet of.
4th plug @ ft. deep 15 sx. in rat or formation with feet of.
5th plug @ ft. deep 10 sx. in mouse or formation with feet of.

(2) Rathole to surface minus 5 feet.

(b) Mousehole to surface minus 5 feet

Fill water well if one is used.

Table with columns: PUSHER, TD, SURFACE PIPE, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @ FT. W/ SX, 2nd PLUG @ FT. W/ SX, 3rd PLUG @ FT. W/ SX, 4th PLUG @ FT. W/ SX, RAT HOLE CIRCULATED W/ SX, MOUSE HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ SX

CEMENT COMPANY Allied pumps
Steve Durant gave or bent
TECHNICIAN Paul Luthie saw all
60/40 w/ 2% gel
OEW 3:00 PM
RECEIVED STATE CORPORATION COMMISSION
NOV 4 1988
CONSERVATION DIVISION Wichita Kansas

15-033-20 735