

10-29-88

To: 070605
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 033-20,733 - 0000
C NW NE, SEC. 17, T 32 S, R 17 W/E
4620 feet from S section line
1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 5428
Operator: Graves Drilling Company, Inc.
Name & Address: 151 North Main, Suite 850
Wichita, KS 67202

Lease Name Peoples Well # 1
County Comanche 190.13
Well Total Depth 5850 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 646

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A

Other well as hereinafter indicated _____

Plugging Contractor Pickrell Drilling Company License Number 5123

Address 110 North Market, Suite 205, Wichita, KS 67202

Company to plug at: Hour: 1:30 a.m. Day: 29 Month: 10 Year: 19 88

Plugging proposal received from Doyle Folkers

(company name) Pickrell Drilling Company (phone) 316-262-8427

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2080'

1st plug at 1100' with 50 sx cement, 2nd plug at 660' with 40 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED

NOV 1 1988

Plugging Proposal Received by Dan Goodrow (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None

Operations Completed: Hour: 3 a.m. Day: 29 Month: 10 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 1100' with 50 sx cement,

2nd plug at 660' with 40 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(if additional description is necessary, use BACK of this form.)

INVOICED (do not) observe this plugging.

DATE 11-3-88

Signed Dan Goodrow (TECHNICIAN)

INV. NO. 22864
10-29

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. 10-13-88 month day year

API Number 15-033-20,733-0000

OPERATOR: License # 5428 Graves Drilling Co., Inc. Name 151 N. Main, Suite 850 Address Wichita, KS 67202 City/State/Zip Contact Person Karen L. Seiler Phone 316-265-7233

C NW NE 17 32 17 East X West Sec. Twp. S. Rg. Ft. from South Line of Section 4620 1980 Ft. from East Line of Section

CONTRACTOR: License # 5123 Pickrell Drilling Company Name Wichita, KS 67202 City/State

(Note: Locate well on Section Plat on reverse side)

Well Drilled For: X Oil Storage Infield Mud Rotary X Gas Inj Pool Exl Air Rotary OWWO Expl Wildcat Cable

Nearest lease or unit boundary line 660 feet County Comanche Lease Name Peoples Well # 1 Ground surface elevation 2080' (Topo) feet MSL

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 10-10-88 Signature of Operator or Agent Richard M. Lusk Title Geologist

Depth to bottom of fresh water 230 Depth to bottom of usable water 600

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 250' feet per Alt. 1 This Authorization Expires 1-10-89 Approved By LKM 10-10-88

Surface pipe by Alternate: X 2 Surface pipe planned to be set 650'

Conductor pipe required Projected Total Depth 5800' Formation Simpson

EFFECTIVE DATE: 10-15-88

SPUD 10-14-88 11:31 AM

Formation Simpson

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

- Cement with 60/40 Posmix, 6% Gel 1090' 1st plug @ ft. deep 680' or formation with w/50 SX. 2nd plug @ ft. deep 40-0' or formation with w/10 SX. 3rd plug @ ft. deep 15 sx. in rat or formation with 4th plug @ ft. deep 10 sx. in mouse or formation with 5th plug @ ft. deep (2) Rathole to surface minus 5 feet *fill water well if one is used (b) Mousehole to surface minus 5 feet

C NW NE 17 32 17 East X West Sec. Twp. S. Rg.

Table with columns: PUSHER (Doyle Folkers), TD (5850'), FORMATION (Simpson), SURFACE PIPE (8 5/8" @ 646'), ANHYDRITE (ELEVATION 2080'), STARTING TIME & DATE (1:31 AM 10-29-88), COMPLETION TIME & DATE (3:00 AM 10-29-88), 1st PLUG @ 1100 FT. W/ 50 SX, 2nd PLUG @ 660 FT. W/ 40 SX, 3rd PLUG @ 40 FT. W/ 10 SX, 4th PLUG @ FT. W/ SX, RAT HOLE CIRCULATED W/ 15 SX, MOUSE-HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ 60/40 6% CEMENT COMPANY Allied, TECHNICIAN D.G. STATE CORPORATION COMMISSION

RECEIVED NOV 1 1988 CONSERVATION COMMISSION NOV 1 1988 CONSERVATION DIVISION Wichita, Kansas