

To: 1 041255
STATE CORPORATION COMMISSION
Wichita State Office Bldg. - PLUGGING SECTION
130 S. Market, Room 2078
Wichita, KS 67202

API NUMBER 15- 033-20,936 - 0000
70' N. & 180' W of
NE NW SE, SEC. 1, T 33 S, R 18 W/E
2380 feet from S section line
1830 feet from E section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 5293
Operator: Helmerich & Payne, Inc.
Name:
Address: 2606 Fleming.
Garden City, KS 67846

Lease Name Crossbar-Judith Well # 1-1
County Comanche 195.88
Well Total Depth 6027 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 668

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ O&A X
Other well as hereinafter indicated _____

Plugging Contractor Duke Drilling Co., Inc. License Number 5929
Address 310 W. Central, Wichita, KS 67202

Company to plug at: Hour: _____ Day: 30 - Month: - 6 Year: 19 97

Plugging proposal received from Ken
(company name) Helmerich & Payne, Inc. (phone) 316-276-3693

Work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 975'
1st plug at 975' with 50 sx cement, 2nd plug at 690' with 50 sx cement,
3rd plug at 40' with 10 sx cement,
4th plug to circulate rathole with 15 sx cement,
5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Pfeifer (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 8:45 p.m. Day: 30 Month: 6 Year: 19 97

ACTUAL PLUGGING REPORT 1st plug at 975' with 50 sx cement,
2nd plug at 690' with 50 sx cement,
3rd plug at 40' with 10 sx cement,
4th plug to circulate rathole with 15 sx cement,
5th plug to circulate mousehole with 10 sx cement.

RECEIVED
KANSAS CORP COMM
1997 JUL -2 11:50

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(If additional description is necessary, use BACK of this form.)

INVOICED
I (did not) observe this plugging.
DATE JUL 03 1997
INV. NO. 48475
6-30

Signed Stephen J. Pfeifer (TECHNICIAN)

EFFECTIVE DATE: 6-10-97

DISTRICT # 1

GA? Yes No

State of Kansas

NOTICE OF INTENTION TO DRILL 033-20,936 ~~0000~~ ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well.

Expected Spud Date 6 14 1997
month day year

Spot 70' N & 180' W of East
NE NW SE Sec 1 Twp 33 S, Rg 18 West

OPERATOR: License # 5293
Name: Helmerich & Payne, Inc.
Address: 2606 Fleming
City/State/Zip: Garden City, Kansas 67846
Contact Person: Ken Jehlik
Phone: (316) 276-3693

2380 feet from South / North line of Section
1830 feet from East / West line of Section

IS SECTION REGULAR IRREGULAR
(NOTE: Locate well on the Section Plat on Reverse Side)

CONTRACTOR: License #: 5929
Name: Duke Drilling

County: Commanche
Lease Name: Crossbar-Judith Well # 1-1
Field Name: W/C

Is this a Prorated/Spaced field? yes no
Target Formation(s): Miss Viola

Well Drilled For: Well Class: Type Equipment:
... Oil ... Enh Rec ... Infield Mud Rotary
 Gas ... Storage ... Pool Ext. ... Air Rotary
... OAWO ... Disposal Wildcat ... Cable
... Seismic; ... # of Holes ... Other

Nearest lease or unit boundary: 1830
Ground Surface Elevation: 1921 feet MSL

Water well within one-quarter mile: yes no
Public water supply well within one mile: yes no

Depth to bottom of fresh water: 180
Depth to bottom of usable water: 200

Surface Pipe by Alternate: 1 2
Length of Surface Pipe Planned to be set: 650

Length of Conductor pipe required: 80
Projected Total Depth: 6000

Formation at Total Depth: Arbuckle
Water Source for Drilling Operations:
... well farm pond other

If OAWO: old well information as follows:
Operator:
Well Name:
Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes no
If yes, true vertical depth:

Will Cores Be Taken?: yes no
If yes, proposed zone:

Bottom Hole Location:
Exp. 12/5/97

220' Alt. I Re 1830

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following information is true and correct:

Pusher Ken

SPUD DATE 6-11-97 INIT. 24

LENGTH SURFACE PLANNED 650

RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE

SURFACE PIPE 8 3/8 @ 16 1/8 CONDUCTOR

ANHYDRITE T- B-975 ELEVATION 500'

TD 6029 FORMATION

RAN PIPE @ SX DV TOOL SX ALT II DONE Y N

IF Need Top Arbuckle Plug @ 40 Ft. W/ SX

Hug./Council @ 40 Ft. W/ SX

Anhydrite Base @ 975 Ft. W/ 50 SX

1/2 Base Anyh. @ 40 Ft. W/ SX

1/2, 1/2 Plug @ 40 Ft. W/ SX

Bottom Surface @ 690 Ft. W/ 50 SX

40' Plug @ 40 Ft. W/ 10 SX

RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ 10 SX

WATER WELL SX (Irr. Well Pond)
Hauling

TECHNICIAN SP DATE 6-27-97

TYPE OF CEMENT 60/40 Poz 6 1/2 gel

STARTING TIME : (AM/PM) DATE

COMPLETION TIME 8:45 (AM) DATE 6-30-97

CEMENT COMPANY Alvied

RECEIVED
KANSAS CORP COMM
JUL 1 1997
A 11:58