

1 070628

DEC 18 1988

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 033-20,739 - 0000
75' E of
SW NW NW , SEC. 19 , T 33 S, R 17 W/EX

TECHNICIAN'S PLUGGING REPORT

Operator License # 3667

Operator: Source Petroleum, A Division of
Name & Address Presley Petroleum Company
200 West Douglas, Suite 820
Wichita, Ks 67202

4290 feet from S section line
4875 feet from E section line

Lease Name Einsel "A" Well # 1

County Comanche 195,81

Well Total Depth 6025 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 420

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Allen Drilling Company License Number 5418

Address Box 1389, Great Bend, KS 67530

Company to plug at: Hour: 7 a.m. Day: 18 Month: 12 Year: 19 88

Plugging proposal received from Gary Christopher

(company name) Allen Drilling Company (phone) 316-793-5681

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1894'
Anhydrite 860-894'

1st plug at 900' with 50 sx cement,

2nd plug at 440' with 40 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Dan Goodrow
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 9 a.m. Day: 18 Month: 12 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 900' with 50 sx cement,

2nd plug at 440' with 40 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED
CONSERVATION COMMISSION

RECEIVED
STATE CORPORATION COMMISSION

DEC 18 1988

DEC 21 1988
12-21-88

CONSERVATION DIVISION
Wichita, Kansas

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.

(If additional description is necessary, use BACK of this form.)

(and note) observe this plugging.

DEC 22 1988

Signed Dan Goodrow
(TECHNICIAN)

DATE

INV. NO. 23451

12-18

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date: 12/12/88

API Number 15-033-20,739-0000

OPERATOR: License # 3667, Name Source Petroleum, A Division of Presley Petroleum Co., Address 200 W. Douglas, Suite #820, City/State/Zip Wichita, Kansas 67202, Contact Person John D. Howard, Jr., Phone 316/262-7397

*75' E of SW, NW, NW, Sec. 19, Twp. 33, S. Rg. 17, East X West, 4290' Ft. from South Line of Section, *4875' Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line *320' 405' feet, County Comanche

CONTRACTOR: License # Unknown, Name Allen Drilling, City/State

Lease Name Einsele "A", Well # 1

Well Drilled For: X Oil, Storage, Infield, Mud Rotary, Gas, Inj, Pool Ext, Air Rotary, OWWO, Expl, Wildcat, Cable

Ground surface elevation 189' 89' feet MSL, Domestic well within 330 feet: yes X no

Municipal well within one mile: yes X no, Depth to bottom of fresh water 180'

Depth to bottom of usable water 200', Surface pipe by Alternate: 1 X 2

If OWWO: old well info as follows: Operator, Well Name, Comp Date, Old Total Depth

Surface pipe planned to be set 220', Conductor pipe required None

Projected Total Depth 6,000' feet, Formation Arbuckle

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 11/28/88, Signature of Operator or Agent, Title General Manager

For KCC Use: Conductor Pipe Required 220' feet; Minimum Surface Pipe Required 220' feet per Alt. 1 d, This Authorization Expires 5-18-89, Approved By LKM, 11-28-88, GRIG. RCVD: 11-18-88

EFFECTIVE DATE: 11-23-88

*WAS: SW-NW-NW, 1950' FEL, 330' FROM BOUNDARY

Set 415' of 8 5/8 on 12-1-88

RECEIVED STATE CORPORATION COMMISSION

DEC 21 1988 12-21-88

CONSERVATION DIVISION Wichita, Kansas

lost circulation @ 5710

PUSHER Gary Christopher

TD 6025 FORMATION Arbuckle

SURFACE PIPE 8 5/8 @ 420'

ANHYDRITE 860'-884' ELEVATION 1894'

STARTING TIME & DATE 7:00 am 12-18-88

COMPLETION TIME & DATE 9:00 am 12-18-88

1st PLUG @ 900 FT. W/ 50 SX

2nd PLUG @ 440 FT. W/ 40 SX

3rd PLUG @ 40 FT. W/ 10 SX

4th PLUG @ FT. W/ SX

RAT HOLE CIRCULATED W/ 15 SX

HOUSE HOLE CIRCULATED W/ SX

WATER WELL PLUGGED W/ SX

CEMENT COMPANY BIT Tital

TECHNICIAN D.G.

60/40 6%

if more than 50' into Arb - 40 SX.