

1070089

TO: STATE CORPORATION COMMISSION /-7

API NUMBER 15-033-20,986-0000  
C NE NE SEC. 17, T 33 S, R 19 W

CONSERVATION DIVISION - PLUGGING SECTION 4620 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 660 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202 LEASE NAME LINDSAY WELL # 1

TECHNICIAN'S PLUGGING REPORT COUNTY COMANCHE

OPERATOR LICENSE # 5428 WELL TOTAL DEPTH 6100 198.25 FEET

OPERATOR: GRAVES DRILLING CO., INC PRODUCTION CSG: SIZE " FEET

NAME AND PO BOX 8250 SURFACE CASING: SIZE 8 5/8" @ 983' WITH SX

ADDRESS WICHITA, KS 67208

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL D/A X

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR DUKE DRILLING CO, INC LICENSE NUMBER 5929

ADDRESS 100 S MAIN, STE 410, WICHITA, KS 67202-3737

COMPANY TO PLUG AT: HOUR: 3:00 PM DAY: 07 MONTH: 01 YEAR: 1999

PLUGGING PROPOSAL RECEIVED FROM JOHN

(COMPANY NAME) DUKE DRILLING CO, INC (PHONE) 316-267-1331

WERE:

1ST PLUG AT 1010' WITH 50 SX CEMENT.

2ND PLUG AT 450' WITH 30 SX CEMENT.

3RD PLUG AT 0-40' WITH 10 SX CEMENT.

4TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

PLUGGING PROPOSAL RECEIVED BY SCOTT ALBERG

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL PART NONE X

OPERATIONS COMPLETED: HOUR: 5:15 PM DAY: 07 MONTH: 01 YEAR: 1999

ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE

1ST PLUG AT 1010' WITH 50 SX CEMENT.

2ND PLUG AT 450' WITH 30 SX CEMENT.

3RD PLUG AT 0-40' WITH 10 SX CEMENT.

4TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

RECEIVED  
STATE CORPORATION COMMISSION

JAN 12 1999  
1-12-99  
CONSERVATION DIVISION  
Wichita, Kansas

REMARKS: USED 60/40 POZMIX 6% GEL BY HALLIBURTON  
(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I DID NOT OBSERVE THIS PLUGGING.

SIGNED

(TECHNICIAN)

FORM CP-2/3

1-15-99  
60546

1-7