

1031541

TO: STATE CORPORATION COMMISSION

API NUMBER 15-033-21,061 - 0000
80'S E/2 SW SW SEC. 26, T 33 S, R 19 W

CONSERVATION DIVISION - PLUGGING SECTION 580 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 1010 FEET FROM WEST SECTION LINE

WICHITA, KANSAS 67202

LEASE NAME SELZER WELL # 26-13

TECHNICIAN'S PLUGGING REPORT

COUNTY COMANCHE 2/12, 88

OPERATOR LICENSE # 3882

WELL TOTAL DEPTH 6550 FEET

OPERATOR: SAMUEL GARY JR., & ASSOC. PRODUCTION CSG: SIZE " FEET

NAME AND ADDRESS 1670 BROADWAY, SUITE 3300 SURFACE CASING: SIZE 8 5/8" @ 663' WITH SX

ADDRESS DENVER, CO 80202-4838 CONDUCTOR CSG: SIZE 20" @ 82'

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL D/A X

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR DUKE DRILLING LICENSE NUMBER 5929

ADDRESS 100 S MAIN, SUITE 410 WICHITA, KS 67202-3737

COMPANY TO PLUG AT: HOUR: 5:00 AM DAY: 16 MONTH: 02 YEAR: 2000

PLUGGING PROPOSAL RECEIVED FROM KEN MCGUIRE

(COMPANY NAME) DUKE DRILLING (PHONE) 316-267-1331

WERE:

1ST PLUG AT 6470' WITH 50 SX CEMENT. 2ND PLUG AT 690' WITH 50 SX CEMENT.

3RD PLUG AT 40'-0' WITH 10 SX CEMENT. 4TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

PLUGGING PROPOSAL RECEIVED BY STEVE DURRANT

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL PART NONE X

OPERATIONS COMPLETED: HOUR: 6:00 AM DAY: 16 MONTH: 02 YEAR: 2000

ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE

1ST PLUG AT 6470' WITH 50 SX CEMENT. 2ND PLUG AT 690' WITH 50 SX CEMENT.

3RD PLUG AT 40-0' WITH 10 SX CEMENT. 4TH PLUG TO CIRCULATE HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

RECEIVED
STATE CORPORATION COMMISSION
2-18-00
FEB 18 2000

REMARKS: USED 60/40 POZMIX 6% GEL BY ALLIED. CONSERVATION DIVISION

(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I DID NOT OBSERVE THIS PLUGGING.

DATE 2/18/00 SIGNED Steve Durrant

(TECHNICIAN)

FORM CP-2/3

WV. NO. 061270

