TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 130 SOUTH MARKET, SUITE 2078 WICHITA, KANSAS 67202

API Well Number: <u>15-163-23416-00-00</u>

Spot: <u>W2NWNE</u>

Sec/Twnshp/Rge: 10-9S-19W

660 feet from N Section Line,

2255 feet from E Section Line

Lease Name: BARRY A

Well #: 1

Operator License No.: <u>5552</u>
On Name: GORE OIL COMPANY

County: ROOKS

Total Vertical Depth: 3584 feet

Op Name: GORE OIL COMPANY

Address: 202 S ST FRANCIS PO BOX 2757
WICHITA, KS 67202

String Si	<u>ze</u> <u>Depth</u>	(ft) Pulled (ft) Comments
PROD 5.5	3579	150 SX
SURF 8.6	25 210	150 SX

Well Type: OIL

UIC Docket No:

Date/Time to Plug: 07/10/2014 9:30 AM

Plug Co. License No.: 99996

Plug Co. Name: ALLIED CEMENT COMPANY

Proposal Revd. from: LENNY DINKEL

Company: GORE OIL

Phone: (785) 259-1928

Proposed P-C @ 1488' w/ 150sx SMD; Production Perfs: 3486'-3488', Ordered 425 sx 60/40 poz mix 4% gel cement w/400# hulls. Plugging Method:

Plugging Proposal Received By: <u>RICHARD WILLIAMS</u>

Date/Time Plugging Completed: <u>07/10/2014 11:00 AM</u>

WitnessType: COMPLETE (100%)

KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Perfs:

3486

Bot

3488

Thru

Comments

Allied pumped 350 sx cement w/400 # hulls. Maximum pressure 500 psi. Shut in pressure 500 psi. Hooked up to back side with instant pressure at 300 psi.

KCC WICHITA

JUL 2 1 2014

RECEIVED

Remarks: ALLIED

Plugged through: CSG

((202.12

District: 04

Signed Richard Welle

7.23.14 CKM (TECHNICIAN)

CM